



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **SANTA FE**
Lease No. **USA 070056**
Unit **C**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

CEU

8-21

1959

Well No. **4** is located **650** ft. from **N** line and **1980** ft. from **E** line of sec. **6**

N 1/4 OF NW 1/4 Sec. 6.
(1/4 Sec. and Sec. No.)

25 North
(Twp.)

12 West
(Range)

N.M. P.M.
(Meridian)

BISTI LOWER CALLUP
(Field)

SAN JUAN
(County or Subdivision)

NEW MEXICO
(State or Territory)

The elevation of the derrick floor above sea level is **5126** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We drill 12 1/2" hole to 314'. Set 8-5/8" OD 24 J-55 Csg. at 311' with 200 sz. cement. Cement circulated - WOC 24 hrs. - Tested csg. to 1000' for 30 min.

We then drill a 7-7/8" hole to 5000'. Set 4 1/2" OD 9.5 J-55 csg. at 5000' with 300 sz. Pozmix cement. Top of cement at 3500' by temperature survey. WOC 48 hrs. Tested csg. to 1000' for 30 min.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company _____

Address _____

By **GURRAY AND CONTINENT OIL CO.**

Title **Asst. Mgr. Operations**

ENGINEER

GPO 662040