Ferm 3160-5 (November 1983) (Formerly 9-331)

UNITED STATES DEP

NOTICE OF INTENTION TO:

SUBMIT IN TRIPLICATE. instructions on

Budget Bureau No. 1004-0135 Expires August 31, 1985

REPAIRING WELL

ARTMENT OF THE INTERIOR verse side)	5, LEASE DESIGNATION AND SERIAL NO.
	NM 070322
	6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NC (Do not use this form for pro- Use "APPLI	OTICES AND REPORTS ON WELLS DOSAILS to drill or to deepen or plug back to a different reservoir. CATION FOR PERMIT—" for such proposals.)	O. I. INDIAN, ADDOTT	E OR IRIDE WAR	
I. OIL GAS [V]		7. UNIT AGREEMENT N	AME	
WELL GAS WELL OTHER				
2. NAME OF OPERATOR		8. FARM OR LEASE NA	ME	
Hixon Development Con	mpany sác so masama mixud			
3. ADDRESS OF OPERATOR	N.V	9. WELL NO.		
PO Box 2810, Farming	332-10			
4. LOCATION OF WELL (Report location	10. FIELD AND POOL, OR WILDCAT Basin Fruitland Coal 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
See also space 17 below.) At surface				
1990' FNL, 1650' FEL, Sec. 10, T25N, R12W, NMPM				
		Sec. 10, 25	R. R12W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, CR, etc.)	12. COUNTY OR PARISI	H 13. STATE	
	6231' GLE	San Juan	New Mexico	
16. Check	Appropriate Box To Indicate Nature of Notice, Report, o	or Other Data		

PULL OR ALTER CASING WATER SHUT-OFF TEST WATER SHUT-OFF ALTERING CASING PRACTURE TREATMENT MULTIPLE COMPLETE FRACTURE TREAT SHOOTING OR ACIDIZING ABANDONMENT* ABANDON* SHOOT OR ACIDIZE Drilling Progress CHANGE PLANS REPAIR WELL (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) (Other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded surface at 11:30 a.m. on March 14, 1990. Drilled 8-3/4" hole to 127'. Ran 3 jts. (125.97') of 7", 20#, J-55, 8rd, ST&C casing. Casing set at 122.74'. Cemented casing as follows: Mixed and pumped 120 sks. (141.6 cu. ft.) Class "B" cement containing 3% CaCl2, no cement returns to surface. Pumped 50 sks. (59 cu. ft.) down backside, cement at surface. Pressure tested casing to 600 psi for 30 minutes. Test ok.



ACCEPTED FOR RECORD

SUBSCOUENT SEPORT OF:

APR 20 1990

FARMINGTON RESOURCE AREA

18. I hereby certify that the foregoing is true and correct	t				_
SIGNED CLARIC RUCHERA NOH	String-	President	DATE _	April 19, 199	0 —
(This space for Federal or State office use)					
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE _	No.	DATE _	· · · · · · · · · · · · · · · · · · ·	
		\$ 1 8 mm			

NUNCO

*See Instructions on Reverse Side