

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE\*

(See other instructions on reverse side)

FOR APPROVED  
OMB NO. 1004-0137  
Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.  
NM 61273

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.  
West Bisti Coal 23 No. 1

9. API WELL NO.

10. FIELD AND POOL, OR WILDCAT  
Basin Fruitland Coal

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 23, T25N, R13W

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

WELL COMPLETION OR RECOMPLETION REPORT AND LOG \*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other \_\_\_\_\_

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REVR. ☐ Other \_\_\_\_\_

2. NAME OF OPERATOR  
Giant Exploration & Production Company

3. ADDRESS AND TELEPHONE NO.  
P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*  
At surface 2510' FNL, 1850' FEL, Sec. 23, T25N, R13W

At top prod. interval reported below

At total depth

RECEIVED  
MAR 25 1993  
OIL CON. DIV  
DIST. 3

14. PERMIT NO. DATE ISSUED

15. DATE SPUDDED 09-08-92 16. DATE T.D. REACHED 09-10-92 17. DATE COMPL. (Ready to prod.) 9-30-92 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)\* 6385' GLE 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 1366.49' 21. PLUG BACK T.D., MD & TVD 1330.49' 22. MULTIPLE COMPL., HOW MANY\* 23. INTERVALS DRILLED BY ROTARY TOOLS X CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)\* 1197' - 1215' 25. WAS DIRECTIONAL SURVEY MADE yes

26. TYPE ELECTRIC AND OTHER LOGS RUN Compensated Density - Neutron logs with Gamma Ray 27. WAS WELL CORED no

28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
7"	20#	128'	8-3/4"	See Exhibit "A" 60	71
4-1/2"	9.5#	1366.49'	6-1/4"	See Exhibit "A" 155	25'

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					1-1/2"	1189'	

31. PERFORATION RECORD (Interval, size and number)				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
INTERVAL	SIZE	NUMBER		DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1197' - 1215'	.40"	72 holes		1197'-1215'	Fraced with 5,400# 40/70 Arizona Sand, 54,000# 12/20 Arizona Sand

33.* PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
01-13-93		Flowing				Shut-in	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
02-11-93	24	1/4"		0	0	0	
FLOW. TUBING PRBS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
0	170		0	0	0	0	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) Sold TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

SIGNED John C. Corbett TITLE Vice President

ACCEPTED FOR RECORD

DATE 3/8/93

\*(See Instructions and Spaces for Additional Data on Reverse Side)

MAR 23 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within the jurisdiction of such department or agency.

BY

SM

WEST BISTI COAL 23 WELL NO. 1  
2510' FNL, 1850' FEL  
SECTION 23, TOWNSHIP 25 NORTH, RANGE 13 WEST  
LEASE NO. NM 61273  
SAN JUAN COUNTY  
NEW MEXICO  
COMPLETION REPORT  
EXHIBIT "A"

CEMENT RECORD

- Surface Casing - Mixed and pumped 60 sks. (70.8 cu.ft.) of Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface.
- Production Casing - Mixed and pumped 80 sks. (164.8 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 75 sks. (85.5 cu.ft.) of Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface.