Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

FORM	I APPR	OVED	
Budget Bure	eau No.	1004-01	35
Expires:	March	31, 1993	

Lease 1	esign	ation	and Se	eriai	INC	٠.
MOO	0	1 /	20	20	1	,

	ill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	Allottee
	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Well X Well Other 2. Name of Operator		8. Well Name and No. Canyon #20E
Cross Timbers Operating Compa	ny	9. API Well No.
3. Address and Telephone No.		30-045-29684
6001 Highway 64, Farmington,	· · · · · · · · · · · · · · · · · · ·	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey D	escription)	Basin Dakota
1540' FSL & 1840' FEL, Sec. 1	3, T25N, R11W, Unit Ltr J s) TO INDICATE NATURE OF NOTICE, REPOR	San Juan Co., NM
		1, on one bank
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing When Running 4-1/2" casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water
Describe Proposed or Completed Operations (Clearly state algive subsurface locations and measured and true vertice).	l pertinent details, and give pertinent dates, including estimated date of starting and depths for all markers and zones pertinent to this work.)*	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Drilled 7-7/8" to 6320', TD, 10/23/98. RU and ran 142 jts 4-1/2", 10.5#, J-55, STC casing and set @ 6317'. RU Dowell/Schlumberger and cemented in 2 stages. First Stage: 600 sx Cl B cement w/3% D79 & 1/4#/sx Celloflake followed w/160 sx Cl B cement w/5#/sx D42 & 1/4#/sx Celloflake. Displaced w/100 bbls fresh water. Plug down @ 8:45 p.m., 10/23/98 w/500 psig, did not bump plug. Float held OK. Opened DV tool w/500 psig. Circulated for 4-1/2 hrs. Did not circulate cement. Second Stage: 325 sx C1 B cement w/3% D79 & 1/4#/sx Celloflake followed w/100 sx Cl B cement w/5#/sx D42 & 1/4#/sx Celloflake. Displaced w/39 bbls fresh water. Plug down @ 2:15 a.m., 10/24/98 w/2,000 psig. Float held OK irculated 10 sx cement to surface. ND BOP. Set slips. Cut off rig @ 6:00 a.m., 10/24/98. WOC.

DVT tool @ 2482'.

OIL CON. DIV.

. I hereby certify that the foregoing is true and correct		- Married Bride - Company Comp
Signed Bolby L Smith		Drilling/Operations Manager Date 10/28/98
(This space for Federal or State office use Bobby L. State of Stat	m1th Title	ACCEPTED FOR HEGORI
Conditions of approval, if any:		NOV 05 1998