Form 9-381 b (April 1952)

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency Jicarilla Apache

Allottes Superior Oil Co.

Lease No. Acarilla Contract

*	#87
SUNDRY	NOTICES AND REPORTS ON WELCEIVED
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF UL 2 9 1959
NOTICE OF INTENTION TO CHANGE PL	
IOTICE OF INTENTION TO TEST WATE	and an amount of the state of t
IOTICE OF INTENTION TO REDRILL OF	[[] [] [] [] [] [] [] [] [] [
OTICE OF INTENTION TO SHOOT OR	ACIDIZE SUBSEQUENT REPORT OF ABANDONMENT.
OTICE OF INTENTION TO PULL OR A	-
OTICE OF INTENTION TO ABANDON V	WFLI
(INDICATE)	E ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	** **
	July 24, 1959
usy Results	1 320 c (F)
eli INO. 335-065 assem 18 loca	ated 320 ft. from S line and 790 ft. from E line of sec 1
SE SE of Section 15	
(14 Sec. and Sec. No.)	(Twp.) (Range) (Meridian)
Wildcat	Rio Afriba New Mexico IIII : 0 1259
(Field)	(County or Subdivision) (State or Tarritory)
(Field)	CH COM COM
(Field)	floor above sea level is 7367 ft. (State or Territory) OIL CON. COM DIST. 3
(Field)	OIL CON. COM
(Field) ne elevation of the derrick	floor above sea level is 7367 ft. DETAILS OF WORK
(Field) The elevation of the derrick is a constant of the depths to the	floor above sea level is 7367 ft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)
(Field) te elevation of the derrick for the names of and expected depths to expect depths	floor above sea level is 7367 ft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet.
(Field) te elevation of the derrick in the names of and expected depths to expected depths to expected 193 feet (5and-waterfraced w	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 9004 (20-40). Average injection
(Field) e elevation of the derrick in the names of and expected depths to the contract of the	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 9004 (20-40). Average injection ours 2300-4000 psig.
(Field) e elevation of the derrick in the names of and expected depths to a seriorated 19) feet (5and-waterfraced wrate 15 BPM. Press C:caned up frac water	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 9004 (20-40). Average injection
(Field) te elevation of the derrick for the names of and expected depths to expected depths to expected depths to expected if a feet of Sand-Waterfraced wrate if BPM. Free Cleaned up frac water is scure noted.	floor above sea level isft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 9004 (20-40). Average injection ours 2500-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight
(Field) te elevation of the derrick is ate names of and expected depths to a erforated 19 feet (5and-waterfraced wrate 15 BPM. Press Cleaned up frac water oil scure noted. Faced cast iron brid	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 9004 (20-40). Average injection ours 2300-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet ce ment on top.
(Field) te elevation of the derrick in the names of and expected depths to the erforated 19 feet (Sand-Waterfraced wrate 15 BPM. Present Cleaned up frac water it scure noted. Laced cast iron brid Cut and pulled 4 1/2.	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, sementing points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 000 gailons and 20, 000f (20-40). Average injection pure 2500-4060 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet comest on top.
(Field) te elevation of the derrick in the names of and expected depths to expected depths to expected depths to expected 19 feet (5 5and - waterfraced wrate 15 5PM. Present is sure noted. The action of the derrick in the second up frac water is sure noted. The action of the derrick in the second cast iron bride.	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, sementing points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 000 gailons and 20, 000f (20-40). Average injection pure 2500-4060 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet comest on top.
(Field) te elevation of the derrick in the names of and expected depths to a seriorated 193 feet (Sand-Waterfraced wrate 15 BPM. Prese Cleaned up frac water in scure noted. Faced cost iron brid Cut and pulled 4 1/2. Cut and pulled 7 5/3	floor above sea level isft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 900f (20-40). Average injection sure 2500-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet ce ment on top. "liner from 5592 feet. "casing from 980 feet.
(Field) te elevation of the derrick in the names of and expected depths to the erforated 19.3 feet (Sand-Waterfraced wrate 15 BPM. Prese Cleaned up frac water in the cure noted. The aced cast from brid Cut and pulled 4 1/2. Cut and pulled 7 5/3. Placed 65 sacks cere	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, sementing points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 000 gailons and 20, 000f (20-40). Average injection pure 2500-4060 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet comest on top.
(Field) te elevation of the derrick is at names of and expected depths to a erforated 19 / feet (5 and - waterfraced w rate 15 BPM. Prese Cleaned up frac water oil scure noted. Faced cast from brid Cut and pulled 4 1/2. Cut and pulled 7 5/3. Placed 65 sacks compulation marker.	floor above sea level isft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50,000 gailone and 20,000f (20-40). Average injection sure 2300-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet cement on top. "liner from 5592 feet. "casing from 980 feet, reent plug 1100-300 feet and 10 sack plug at surface with re-
(Field) te elevation of the derrick is at names of and expected depths to a erforated 19 / feet (5 and - waterfraced w rate 15 BPM. Prese Cleaned up frac water oil scure noted. Faced cast from brid Cut and pulled 4 1/2. Cut and pulled 7 5/3. Placed 65 sacks compulation marker.	floor above sea level isft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailone and 20, 900f (20-40). Average injection sure 2500-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet ce ment on top. "liner from 5592 feet. "casing from 980 feet.
(Field) te elevation of the derrick is ate names of and expected depths to a erforated 19 feet (Sand-Waterfraced wrate 15 BPM. Prese Cleaned up frac water oil scure noted. Faced cast iron brid Cut and pulled 4 1/2. Cut and pulled 7 5/3. Placed 65 sacks computation marker. Filled between pluge.	floor above sea level isft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50,000 gailone and 20,000f (20-40). Average injection sure 2300-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet cement on top. "liner from 5592 feet. "casing from 980 feet, reent plug 1100-300 feet and 10 sack plug at surface with re-
ce elevation of the derrick in the names of and expected depths to erforated 19. feet (Sand-Waterfraced wrate 15 BPM. Freed Cleaned up frac water is acid scure noted. Cut and pulled 4 1/2. Cut and pulled 7 5/3. Placed 65 sacks cerrulation marker. Filled between pluge understand that this plan of weeks.	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 900 gailons and 20, 9004 (20-40). Average injection sure 2500-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet coment on top. "liner from 5592 feet. "casing from 980 feet. reset plug 1100-300 feet and 10 sack plug at surface with re- with saud. F. & A 7-24-59.
(Field) e elevation of the derrick in the names of and expected depths to a seriorated 19.3 feet (Sand-Waterfraced wrate 15 BPM. Prese Cleaned up frac water is aced cast from brid Cut and pulled 4 1/2. Cut and pulled 7 5/3 Placed 65 sacks congulation marker. Filled between pluge (understand that this plan of works mpany	floor above sea level is 7367 DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work) Gallup section from 7422 feet to 7940 feet. with 50, 900 gailons and 20, 9004 (20-40). Average injection sure 2500-4060 psig. er and sand to 7775 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet ce ment on top. "liner from 5592 feet. "casing from 980 feet. "casing from 980 feet. with smed. F. & A 7-24-59. must receive approval in writing by the Geological Survey before operations may be commenced. TED CII. & GAS, INC.
(Field) te elevation of the derrick in the names of and expected depths to a seriorated 19.3 feet (Sand-Waterfraced wrate 15 BPM. Prese Cleaned up frac water is aced cast from brid cuts and pulled 4 1/2. Cut and pulled 7 5/3 Placed 65 sacks cerrulation marker. Filled between pluge understand that this plan of works apparay.	floor above sea level is 7367 ft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, ossessing points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 000 gailons and 20, 0004 (20-40). Average injection sure 2500-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dge plug at 6000 feet with 25 feet cement on top. "liner from 5592 feet. "casing from 980 feet. "casing from 980 feet. with mud. F. & A 7-24-59. must receive approval in writing by the Geological Survey before operations may be commenced. FED OIL & GAS, INC. S. National Bank Bidg. CONSOLIDATED OIL & GAS, III
(Field) te elevation of the derrick is to names of and expected depths to a serior ated 19.3 feet (Sand-Waterfraced wrate 15 BPM. Prese Cleaned up frac water is aced cast iron brid Cut and pulled 4 1/2. Cut and pulled 7 5/3 Placed 65 sacks congulation marker. Filled between pluge understand that this plan of weeks many 312 Denver 3	floor above sea level is 7367 ft. DETAILS OF WORK objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, osmenting points, and all other important proposed work) Gallup section from 7422 feet to 7340 feet. with 50, 600 gailons and 20, 000f (20-40). Average injection ours 2300-4000 psig. er and sand to 7375 feet and tested 246 MCFDonly slight dige plug at 6000 feet with 25 feet coment on top. "liner from 5592 feet. "casing from 980 feet. "casing from 980 feet. "with mad. F. & A 7-24-59. must receive approval in writing by the Geological Survey before operations may be commenced. FED GIL & GAS, INC. "S. National Bank Bidg. CONSOLIDATED GIL & GAS, II

Title__