

submitted in lieu of Form 3160-5

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

RECEIVED  
BLM

Sundry Notices and Reports on Wells

1. Type of Well  
GAS

RECEIVED  
JUN - 9 1995

070 FARMINGTON, NM

2. Name of Operator

MERIDIAN OIL

OIL CON. DIV.  
DIST. 3

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1550' FSL, 990' FWL, Sec. 15, T-27-N, R-6-W, NMPM

5. Lease Number  
SF-079365

6. If Indian, All. or  
Tribe Name

7. Unit Agreement Name

San Juan 28-6 Unit

8. Well Name & Number  
San Juan 28-6 U #6

9. API Well No.  
30-039-07048

10. Field and Pool  
Blanco Mesaverde

11. County and State  
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

Notice of Intent

Abandonment

Change of Plans

Subsequent Report

Recompletion

New Construction

Final Abandonment

Plugging Back

Non-Routine Fracturing

Casing Repair

Water Shut off

Altering Casing

Conversion to Injection

Other - Sidetrack workover

13. Describe Proposed or Completed Operations

Procedure change submitted by letter dated 2-2-95, approved by Steve Mason, BLM

- 3-29-95 MIRU. ND WH. Tbg stuck @ approximately 4500-4600'. NU BOP. SDON.
- 3-30-95 RU, ran free point, tbg stuck @ 4880'. Jet cut tbg @ 4860'. RD. TOOH w/155 jts 2 3/8" tbg. TIH w/7" csg scraper to 4743'. TOOH. SDON.
- 3-31-95 TIH w/7" cmt retainer, set @ 4711'. Load tbg w/14 bbl wtr. PT tbg to 2000 psi, OK. Load hole w/120 bbl wtr. Circ clean w/40 bbl wtr. PT csg to 1000 psi/15 min, OK. Leave 500 psi on backside. Establish injection in open hole. Plug #1: pump 294 sx Class "B" neat cmt w/2% calcium chloride below cmt retainer. Pump 5 sx Class "B" cmt w/2% calcium chloride above cmt retainer to 4680'. Displace w/14.5 bbl wtr. Hesitation sqz open hole Mesaverde to 2000 psi. Reverse circ w/36 bbl wtr, received 0.5 bbl cmt. Leave 1 bbl cmt on top of cmt retainer. TOOH. RU. Ran VDL-CBL-CCL @ 0-4681 w/1000 psi, cmt intervals @ 4003-4681, 500-2548' & 242-210'. RD. SD for weekend.
- 4-3-95 TIH to 2420'. TOOH. ND BOP. NU WH. RD. Rig released.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Affairs Date 5/30/95

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_

Date

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

JUN 05 1995

NMOCD

FARMINGTON DISTRICT OFFICE  
BY [Signature]

