## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

## RECEIVED BLM

Sundry Notices and Reports on WellsJUL 20 AN 10:56 070 FARMINGTON, NWISF-079365 If Indian, All. or 1. Type of Well GAS Tribe Name Unit Agreement Name 2. Name of Operator San Juan 28-6 Unit MERIDIAN OIL Well Name & Number 3. Address & Phone No. of Operator San Juan 28-6 U #27 PO Box 4289, Farmington, NM 87499 (505) 326-9700 9. API Well No. 30-039-07087 4. Location of Well, Footage, Sec., T, R, M 10. Field and Pool 995'FNL, 990'FEL, Sec.15, T-27-N, R-6-W, NMPM Blanco Mesa Verde 11. County and State Rio Arriba Co, NM 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA Type of Action Type of Submission Abandonment Change of Plans
Recompletion New Construction \_X\_ Notice of Intent Plugging Back Non-Routine Fracturing
Casing Repair Water Shut off
Altering Casing Conversion to Injection \_\_\_ Plugging Back Subsequent Report \_\_\_ Casing Repair Final Abandonment X Other - Sidetrack workover 13. Describe Proposed or Completed Operations It is intended to workover the subject well in the following manner: TOOH w/tbg. If tbg is stuck, cut off tbg approximately 100' below csg shoe. Set cmt retainer near bottom of 7" csg. TIH w/2 3/8" tbg, CO. Sting into ret. Test tbg to 2500 psi. Sting all the way through ret, load backside w/wtr, PT 500 psi. Squeeze open hole w/cmt. Pull out of retainer. Spot cmt on top of retainer. Pull up one joint, reverse excess cmt out. Run CBL. Perf squeeze holes above TOC. Squeeze cmt to 50'above Ojo Alamo. Drill to 10' below 7" csg shoe. Sidetrack using a downhole motor. Drill to approximately 6000'. Run a full string of 4 1/2" csq & cmt. Selectively perf and frac the Mesa Verde formation and return well to production. I hereby certify that the foregoing is true and correct. Maddel (KAS) Title Regulatory Affairs Date 7/15/94 (This space for Federal or State Office use) \_\_\_\_Title \_\_\_\_ Date APPROVED BY CONDITION OF APPROVAL, if any:

APPROVED 2 1994