

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input type="checkbox"/> Federal <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	San Juan 27-4 Unit
3. Address of Operator	8. Farm or Lease Name
Box 990, Farmington, New Mexico -87401	San Juan 27-4 Unit
4. Location of Well	9. Well No.
UNIT LETTER H, 1750 FEET FROM THE North LINE AND 850 FEET FROM THE East LINE, SECTION 31 TOWNSHIP 27N RANGE 4W NMPM.	46
15. Elevation (Show whether DF, RT, GR, etc.)	10. Field and Pool, or Wildcat
6816' GL	Basin Dakota
12. County	
	Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	


17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled hole to total depth (8145'), stuck casing at 7940' while running in, cut off casing at free point (6100').

Due to the above junk in the hole it is intended to plug back in the following manner:

Spot a 200 sack cement plug on top of the fish at approximately 6050'. Set a drillable cement retainer near the bottom of the 7" casing (3854') and squeeze the open hole with 200 sacks of cement with 1/4 cu. ft. of Gilsonite and 2% gel and 100 sacks of cement with 10% sand and 2% calcium chloride.

A new sidetracked hole will be drilled to approximately 8050'.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original signed by  
Carl E. Matthews

SIGNED TITLE Petroleum Engineer DATE 8-26-68

APPROVED BY SUPERVISOR DIST. #3 DATE AUG 27 1968

CONDITIONS OF APPROVAL, IF ANY: