Form	9-331
(May	1963)

UNITED STATES

DEPARTMENT OF THE INTERIOR (Other Instructions on re- GEOLOGICAL SURVEY					J. LEA	SF 079391		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)				6, IF I	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
1. OIL GAS				1	7. UNIT AGREEMENT NAME			
WELL WEI	WELL WELL A OTHER					San Juan 27-5 Unit		
2. NAME OF OPERATOR					8. FAR	8. FARM OR LEASE NAME		
El Paso Natural Gas Company						San Juan 27-5 Unit		
	3. ADDRESS OF OPERATOR							
PO Box 99	PO Box 990, Farmington, NM 87401							
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)			10. FII	ELD AND POOL, OR	WILDCAT			
At surface 1140'N, 800'W				11. SE	So. Blanco Pictured Cliffs 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
					Sec	Sec. 18, T-27-N, R-5-W		
14. PERMIT NO.	14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. co	UNTY OR PARISH	13. STATE		
			6417'GI		Rio	Arriba	New Mexico	
16.	Check Ap	propriate Box To	Indicate N	lature of Notice, Report, o		-		
	NOTICE OF INTEN	rion to:		SUBS	EQUENT REP	ORT OF:		
TEST WATER SHUT-OFF PULL OR ALTER CASING		э 🗔	WATER SHUT-OFF	X	REPAIRING W	.		
FRACTURE TREAT		AULTIPLE COMPLETE		FRACTURE TREATMENT	_X	ALTERING CA		
SHOOT OR ACIDIZI		BANDON*		SHOOTING OR ACIDIZING		ABANDONMEN		
(Other)		HANGE PLANS		(Other)	ilts of mult mpletion Re	ple completion opert and Log for	n Well m.)	
17. DESCRIBE PROPOSE proposed work. nent to this wor	If well is direction	RATIONS (Clearly stat nally drilled, give su	e all pertinen bsurface locat	t details, and give pertinent da tions and measured and true ver	tes, includin tical depths	g estimated date for all markers	of starting any and zones perti-	
3-1-74	3-1-74 Tested surface casing, held 600#/30 minutes.				4 2			
3-5-74	3-5-74 TD 3322'. Ran 114 joints 2 7/8", 6.4#, J-55 production casing, 3312'						· · · · · · · · · · · · · · · · · · ·	
set at 3322'. Baffle set at 3311'. Cemented with						-	· · · · · · · · · · · · · · · · · · ·	
		hours. Top of cement at 1900'.						
5-23-74	5-23-74 Tested casing to 4000#-OK.							

PBTD 3311'. Perf'd 3206-22', 3246-66' with 19 shots per zone. Frac'd with 46,000# 10/20 sand and 46,518 gallons treated water. Dropped one set of 19 balls. Flushed with 840 gallons water.





18. I hereby certify that the foregoing is true and corre	et	1 and 1
SIGNED A SUCCES	TITLE Drilling Clerk	рать <u>Мау 29, 1974</u>
(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		