STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

,	URLINGTON RESOURC	CES OIL & GAS CO.	Lease SAN JUAN 27	-4 UNIT	Well No. 126			
Location of Well:	Unit L Sect NAME OF	20 Twp. 027N FRESERVOIR OR POOL	Rge. 004W TYPE OF PROD. (Oil or Gas)	County RIO ARRIBA METHOD OF PROD. (Flow or Art. Lift)	PROD. MEDIUM (Tbg. or Csg.)			
Upper Completion	PICTURED CLIFFS		Gas	Flow	Tubing			
Lower Completion	MESAVERDE		Gas	Flow	Tubing			
		PRE-FLOW SHUT	-IN PRESSURE DATA					
Upper Completion	Hour, date shut-in 05/18/2001	Length of time shut-in 72 Hours	SI press. psig	Stabilized? (*	Yes or No)			
•	03/10/2001	72 110413	1.00					
Lower Completion	05/18/2001	120 Hours	217					
			TEST NO. 1					
	at (hour.date)*	05/21/2001		g (Upper or Lower) U	PPER			
TIME	LAPSED TIME	PRESSURE	PROD. ZONE					
(hour.date)	SINCE*	Upper Completion Lower Cor	mpletion TEMP	RE	MARKS			
05/22/2001	96 Hours	181 21	8					
05/23/2001	120 Hours	166 22		UL 2001 ECEIVED IL CON. DIV DIST. 3				
Production rate	e during test							
Oil	BOPD based on	Bbls. in	Hours.	Grav.	GOR			
Gas:		MCFPD; Tested thru (Orifice or M	eter):					
		MID-TEST SHUT	-IN PRESSURE DATA					
Upper Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			
Lower Completion	Hour. date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)			
5333702 302								

FLOW TEST NO. 2

Commenced at (hour, d	ate)**		Zone producing (Upper or Lower):			
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS	
		Upper Completion	Lower Completion	TEMP.	REWARKS	
		-				
			<u></u>			
Production rate du	iring test					
					0.00	
Oil:	E	OPD based on	Bbls. in	Hours	Grav GOR _	
Cias:		MCFP	D: Tested thru (O	rifice or Meter):		
Remarks:						
		-				
I hereby certify th	at the information h	ား ကြ ် ontained is true	e and complete to	the best of my knowledg Operator Burlingt	e.	
	JUL		10	Out and a Publicat	on Dasaumaas	
				Operator Burlingt	/ *	
	Dil Conservation Di			By Whorn A	logo	
9,1	AND THE PROPERTY OF A	CHARLET, PERMA	V		0	
Ву				Title Operations A	ssociate	
05	PUTY OIL & GAS I	NSPECTOR, DIST.	9	Data Thunsday M	ov 24, 2001	
Title			·	Date <u>Thursday, M</u>	ay 44, 4001	

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2 At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note if, on a initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Lest No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests, all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).