UNITED STATES DEPARTMENT OF THE INTERIOR

*1 と D. P. Corton (Magint は) ではなる。

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SE O TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 28-7 Unit 8. FARM OR LEASE NAME
1. oil gas X other	San Juan 28-7 Unit 9. WELL NO.
2. NAME OF OPERATOR El Paso Natural Gas Company	236 10. FIELD CR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, New Mexico 87401	Basin Dakota 11. SEC., T., R., M., OR BLK, AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1550'N, 1085'E	AREA Sec. 6, T-27-N, R-7-W
AT TOP PROD. INTERVAL: AT TOTA_ DEPTH:	Rio Arriba: New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	6178' GL 848 B SHEE IVE
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or 2017) change on Form 9-330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	all pertinent details, and give pertinent dates, rectionally drilled, give subsurface locations and to this work.)*
12-30-78: TD 3006'. Ran 77 jts. 7', 20#, K-55 intermediate casing, 2994! set at 3006'. Cemented w/188 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1700'.	
01-04-79: TD 7175'. Ran 216 jts. 4 1/2", 10.5# & 11.6#, K-55 production casing 7162' set at 7175'. Float collar set at 7159'. Cemented w/641 cu. ft. cement. WOC 18 hours. Top of cement at 2600'.	
05-02-79: PBTD 7159'. Tested casing to 4000#, OK. Perfed Dak. 6950,6956,6962,6968, 7035,7042,7073,7078,7083,7105,7113,7122,7134,7152' w/1 SPZ. Fraced w/123,000# 20/40 sand, 41,000# 10/20 sand and 98,200 gal. treated water. Flushed w/4788 gal. water.	
·	That bar be a side of the side
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED Dilling Clerk DATE May 3, 1979	
(This space for Federal or State office use)	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE SECOND STATE OF THE S