## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5.	<b>5.</b> LEASE			
	SF	07856	5A	١,

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
	7 LINIT ACREMENT NAME			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME San Juan 28-7 Unit			
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME			
	San Juan 28-7 Unit			
1. oil ☐ gas ☒ other	9. WELL NC. 7 2 4 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2			
2. NAME OF OPERATOR	261			
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME			
3. ADDRESS OF OPERATOR	Basin Dakota			
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR			
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 5, T-27-N, R-7-W			
below.)	N.M.P.M.			
AT SURFACE: 1240'S, 2155'W AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE			
AT TOTAL DEPTH:	Rio Arriba New Mexico  14. API NO.			
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)			
Marshin, on onnan anni	6752' GL			
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	OTTE GET			
TEST WATER SHUT-OFF	그 그 그 그는 그 그 그 회회를 가 봤는 중요하다 그 그 것은			
FRACTURE TREAT	그 그 그는 그는 성용화하는 જ 호상임과 그 것이다.			
SHOOT OR ACIDIZE				
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)			
MULTIPLE COMPLETE				
CHANGE ZONES	三十二十二十二年正朝新 一寶 电多复算 一静			
ABANDON*				
(other)				
	1 8 g x 1 9 g x 1			
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d	e all pertinent details, and give pertinent dates,			
measured and true vertical depths for all markers and zones pertiner	nt to this work.)*			
7 Or 70. TD 7054! Dan 02 its 7!! 20# K-55	intermediate casing 3543' set at			
1-05-79: TD 3554'. Ran 92 jts. 7", 20#, K-55 intermediate casing, 3543' set at 3554'. Cemented w/255 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top				
	nodis, hera 1200% 30 minutes. Top			
of cement at 2100'.	그는 그는 그는 일본 중심하는 학교 중심하는 그는 그는 그는 것이 되었다.			
1-12-79: TD 7782'. Ran 231 jts. 4 1/2", 10.5#	& 11.6#, K-55° production casing,			
7771' set at 7782'. Float collar set at 7764'.	Cemented w/647 cu. ft. cement.			
WOC 18 hours. Top of cement at 2900'.				
	OV Domfod Dake 7555 7560 7565			
5-06-79: PBTD 7764'. Tested casing to 4000#,	UN. PETTER DAK. /333,/300,/303,			
7570,7640,7672,7677,7682,7701,7706,7722,7733,77	4/,//55 W/I 5r4. Fraceu W/65,000#			
40/60 sand and 83,000 gal. treated water. Flus	ned w/5000 gal. water.			

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Clerk DATE

(This space for Federal or State office use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: