

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐  
2. NAME OF OPERATOR  
El Paso Natural Gas Company  
3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
1800'S, 810'E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
SF 079393  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
San Juan 27-5 Unit  
8. FARM OR LEASE NAME  
San Juan 27-5 Unit  
9. WELL NO.  
21A (PM)  
10. FIELD OR WILDCAT NAME  
Blanco MV. Blanco PC  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 3, T-27-N, R-5-W  
NMPM  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6683' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-18-80: MOL Set 4 1/2" Packer at 3760'. Pressure tested to 1200#, and set 7" RTTS Packer at 3580'. Tested to 3500#, OK. Cemented w/ 77 cu. ft. cement. WOC 18 hours.

4-21-80: PBDT 6156'. Tested casing to 3500#, OK. Perfed P.L. 5706,5710,5724,5729, 5745,5750,5764,5770,5776,5783,5790,5804,5810,5816,5822,5846,5853,5865,5921, 5930,5978,6000,6050,6064' W/1 SPZ. fraced w/81,000# 20/40 sand, 181,800 gal. wtr. Flushed w/ 7700 gal. wtr.

Perfed C.H. & Men. 5214,5220,5236,5295,5301,5325,5330,5343,5348,5417,5423, 5440,5444,5519,5524,5586,5594,5626' W/1 SPZ. Fraced w/ 55,000# 20/40 sand, 110,000 gal. wtr. Flushed w/7600 gal. wtr.

4-20-80: Perfed PC. 3535-56,3560-82,3600-16' W/16 SPZ. Fraced w/60,000# 10/20 sand, 76,000 Gal. WTR. Flushed w/1000 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED A. J. Duice TITLE Drilling Clerk DATE April 11 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

\*See Instructions on Reverse Side



BY M. L. Kuchera  
FARMINGTON DISTRICT