Form 9–331
Dec. 1973

Form Approved.
Budget Bureau No. 42–R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

1. oil well ☐   gas well ☒   other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1460'S, 1020'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

5. LEASE
SF 079366

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Rincon Unit

8. FARM OR LEASE NAME
Rincon Unit

9. WELL NO.
108 A

10. FIELD OR WILDCAT NAME
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19, T-27-N, R-6-W
N.M.P.M.

12. COUNTY OR PARISH
Rio Arriba

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6509' GL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	☐	☒
FRACTURE TREAT	☐	☐
SHOOT OR ACIDIZE	☐	☐
REPAIR WELL	☐	☐
PULL OR ALTER CASING	☐	☐
MULTIPLE COMPLETE	☐	☐
CHANGE ZONES	☐	☐
ABANDON*	☐	☐
(other)		

(NOTE: Report results of multiple completion or zone change on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-24-79:   PBTD 5736'. Tested casing to 3500#, OK. Perfed P.L. 5257,5290,5309,5314,5319, 5324,5329,5334,5350,5354,5358,5362,5394,5414,5438,5478,5540,5558,5568,5606, 5624,5650,5669,5707' W/1 SPZ. Fraced w/68,000# 20/40 sand, 136,000 gal. wtr. Flushed w/7140 gal. wtr.

10-25-79:   Perfed C.H. & Men. 4718,4752,4760,4768,4776,4784,4796,4802,4807,4921,4930, 4938,4964,4972,4984,5020,5058,5065,5076,5112,5120,5134,5156,5168' W/1 SPZ. Fraced w/ 67,000# 20/40 sand, 134,000 gal. wtr. Flushed w/ 6500 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____   Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE _Drilling Clerk__ DATE __ October 29, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side