

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

CURTIS J. LITTLE

3. ADDRESS OF OPERATOR

P. O. Box 2487  
Farmington NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1800' FSL 2000 FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) spud & surface casing

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



(NOTE: Report results of multiple completion or one change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

SPUD well @ 3:00 PM on 4-22-82. DRLD 9-7/8" hole to 140'. RAN 6 JTS 7" 23# K55 casing measuring 132'7" and set @ 132'GR. Cemented w/60 sx Class B neat w/2% CaCl. Cement circulated to surface. P.D. @ 7:30 PM 4-22-82. 7:30 AM 4-23-82 Pressure tested to 600 psi. Held O.K.

Subsurface Safety Valve: Manu. and Type n/a Set @          Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Agent DATE 5-3-82

(This space for Federal or State office use)

APPROVED BY          TITLE          DATE           
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NM000

RECEIVED FOR RECORD

MAY 5 1982

RECEIVED FOR RECORD

BY SM