

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Turner Production Company  
3. ADDRESS OF OPERATOR  
c/o A. R. Kendrick, Box 516, Aztec, NM 87410  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1460' FSL 790' FEL Section 26  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED  
FEB 22 1983  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.

5. LEASE NM-0111-A  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Turner 26  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME Otero-Chacra & So. Blanco-Pictured Cliffs  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
26, T26N, R7W  
12. COUNTY OR PARISH Rio Arriba  
13. STATE NM  
14. API NO.  
30-039-23111  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
7026 DF . 7026 RDB

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in NOWSCO coiled tubing unit. Jetted with nitrogen as tripped into hole. found bridge @ 3888'. Cleaned out sand and water to 3957' (assumed to be on pin in bottom collar.) SDON.

Well died. Tripped back in jetting with nitrogen. SDON.

Well died. Attempted to drill pin with dynadrill on coiled tubing unit. Mill did not get on pin.

Tripped in hole with tubing while jetting with nitrogen. Found bridge @ 1522' that we could not remove with nitrogen. Trip out of hole. Had pieces of wire in tubing. Shut down for weather. Will pull tubing to remove fish when weather clears and mud dries.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED AR Kendrick TITLE Agent DATE February 22, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC

FEB 28 1983  
Elliott