NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Checking B	Selow
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)
	April 8, 1955	Farmington, New Mexic
Following is a report on the wor	k done and the results obtained under tne heading	noted above at the
Frank A. Schultz, Jr.	• perator)	State (E-6634)
	Co., Ind., Well No. 3-16	
(Contracto	outh Blanco P.C. Pool,	
	Aprilx7;x1955 April 6-7, 195	
Notice of intention to do the work (wa	s) (submitted on Form (100 on	(Cross out incorrect words) 1955
nd approval of the proposed plan (wa		
are approved at the break break (a) (ali i) obtained.	
DETA Spudded well at 5:00 1	LLED ACCOUNT OF WORK DONE AND REST	
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3	ILED ACCOUNT OF WORK DONE AND RES	th cable tool to 104 T.D.
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface.	Joints 8-5/8" OD 24# J-55 casing	th cable tool to 104 T.D. to total depth. Cemented g Halliburton. Circulated to
Spudded well at 5:00 l (96° from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface.	Joints 8-5/8" OD 24# J-55 casing sent and 50 sacks Posmis "S" usin	th cable tool to 104 T.D. to total depth. Cemented g Halliburton. Circulated to
Spudded well at 5:00 l (96° from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface.	Joints 8-5/8" OD 24# J-55 casing sent and 50 sacks Posmis "S" usin	th cable tool to 104 T.D. to total depth. Cemented g Halliburton. Circulated to
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface.	Joints 8-5/8" OD 24# J-55 casing sent and 50 sacks Posmis "S" usin	th cable tool to 104 T.D. to total depth. Cemented g Halliburton. Circulated to
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface. Moved cable tool off.	Joints 8-5/8" OD 24# J-55 casing ment and 50 sacks Permis "S" using Will do further drilling with respectively.	th cable tool to 104 T.D. to total depth. Cemented g Halliburton. Circulated to
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface. Moved cable tool off.	Joints 8-5/8" OD 24# J-55 casing ment and 50 sacks Posmis "S" using Will do further drilling with respect to the following the drilling with respect to the sacks posmis "S" using the drilling with the sacks posmis "S" using the drilling with the sacks posmis "S" using the sacks posmis "S" u	to total depth. Cemented Halliburton. Circulated to otary rig.
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface. Moved cable tool off.	Joints 8-5/8" OD 24# J-55 casing ment and 50 sacks Permis "S" using Will do further drilling with respectively.	to total depth. Cemented g Halliburton. Circulated to otary rig.
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface. Moved cable tool off. Witnessed by Oliver E. Towell (Name)	Joints 8-5/8" OD 21# J-55 casing sent and 50 sacks Posmis "S" using Will do further drilling with recommendation of the drilling with reco	to total depth. Cemented Halliburton. Circulated to otary rig. Company, Inc. Tool Pusher
Spudded well at 5:00 l (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat car surface. Moved cable tool off. Witnessed by Oliver E. Towell (Name) Approved: OIL CONSERVATION	Joints 8-5/8" OD 21# J-55 casing sent and 50 sacks Posmis "S" using Will do further drilling with recommendation of the drilling with reco	to total depth. Cemented Halliburton. Circulated to otary rig. Company, Inc. Tool Pusher (Title) That the information given above is true and complete knowledge.
Spudded well at 5:00 1 (96' from ground). April 7, 1955 - Ran 3 with 50 sacks neat cersurface. Moved cable tool off. Witnessed by Oliver E. Towell (Name) Approved: OIL CONSERVATION Original Signed En	Joints 8-5/8" OD 21# J-55 casing ment and 50 sacks Posmis "S" using Will do further drilling with recommendation of the drilling with reco	to total depth. Cemented Halliburton. Circulated to otary rig. Company, Inc. Tool Pusher

AZTEC DISTRICT ORDES No. Copies Revolved District Control of the	OIL CONSERVA	TION COMI	MISSION
Discourse Discou	AZTEC DIS	Indi ora	SE
Discourse Standard Co. Standard	No. Copies Flans		
Carrier Lanca Fe Description of the carrier C. S. Transporter die	D! (i)		
Carrier Lanca Fe Description of the carrier C. S. Transporter die			
Stanta fe Charten on the se Lists the separate Charten on the separate Only the separate Only the separate of the separat		1	1
Control of the second of the s	- Barry Fe		
v. C. S Stenoporter	iformatury		
Transporter			· · · · · · · · · · · · · · · · · · ·
Trenshorter f	<u> </u>		
ello j	Transporter		
		<u> </u>	
	The second section of the section of the second section of the section of the second section of the secti		المارين والمسايدة
	Ī	ı	1