

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SF 078431

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

NICKSON

9. WELL NO.

17

10. FIELD AND POOL, OR WILDCAT

BASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASEC. 22, T-26N, R-8W,
N.M.P.M.

12. COUNTY OR PARISH

SAN JUAN

13. STATE

NEW MEXICO

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6913 FT. R.K.B.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
REPAIR WELL
(Other)PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANSWATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZINGREPAIRING WELL
ALTERING CASING
ABANDONMENT*(Other) **SUPPLEMENTARY WELL HISTORY** XX
(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. DRILLED 7-7/8" HOLE TO T.D. OF 8175 FT. R.K.B. REACHED T.D. 12/2/67.
2. SET 150 SACKS CEMENT PLUG OVER THE ENTRADA FORMATION FROM 7580 FT. TO 8175 FT. R.K.B. PLUG DOWN AT 3:45 A.M. 12/3/67.
3. RAN 231 JTS. OF 4-1/2", 10.50#, J-55 CASING. LANDED AT 7392 FT. R.K.B. BAKER STAGE COLLARS SET AT 2823 FT. AND 5292 FT. R.K.B. CEMENTED FIRST STAGE WITH 700 CU.FT. OF CLASS "C" CEMENT. PLUG DOWN AT 5:55 A.M. 12/4/67. CEMENTED SECOND STAGE WITH 950 CU.FT. OF CLASS "C" CEMENT. PLUG DOWN AT 6:55 A.M. 12/4/67. CEMENTED THIRD STAGE WITH 1200 CU.FT. CLASS "C" CEMENT. PLUG DOWN AT 7:45 A.M. 12/4/67.
4. RIGGED UP COMPLETION UNIT 12/12/67.
5. RAN 1-1/2" TUBING AND DRILLED OUT STAGE COLLARS AT 2823 FT. AND 5292 FT. R.K.B. CLEANED OUT TO P.B.T.D. OF 7357 FT. R.K.B.
6. PRESSURE TESTED CASING TO 4000 P.S.I. FOR 10 MINUTES. TEST OK.
7. RAN GAMMA RAY CORRELATION AND CEMENT BOND LOG. POOR BOND INDICATED IN DAKOTA.
8. PERFORATED 2 SQUEEZE HOLES AT 7240 FT. AND 6950 FT. R.K.B. RAN 4-1/2" BAKER PACKER AND SET AT 7000 FT. R.K.B. SQUEEZED HOLES AT 7240 FT. WITH 75 SACKS OF CLASS "C" CEMENT. MAX. STANDING PRESSURE 1500 P.S.I. JOB COMPLETE 1:30 P.M. 12/13/67. RESET PACKER AT 6950 FT. R.K.B. SQUEEZED HOLES AT 6950 FT. R.K.B. WITH 75 SACKS OF CLASS "C" CEMENT. MAX. STANDING PRESSURE 1500 P.S.I. JOB COMPLETE 4:00 P.M. 12/13/67.
9. P.B.T.D. 7220 WAITED ON CEMENT UNTIL 10:30 A.M. 12/14/67. PRESSURE TESTED CSG. TO 3500 PSI. TEST OK.
10. PERFORATED FIRST STAGE DAKOTA WITH 1 SHOT PER FT. 7120-7128, 7136-7156, 7182-7186, & 7190-7200. SAND WATER FRAC PERFORATIONS W/55,000# SAND, 1000# GLASS BEADS, & 66,650 GAL. 1% KCL WATER.

18. I hereby certify that the foregoing is true and correct

Original signed by
SIGNED GILBERT D. NOLAND, JR.TITLE DRILLING SUPERINTENDENTDATE DECEMBER 19, 1967

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963 - O-685229

697-651

11. SET 4-1/2" BRIDGE PLUG AT 7085 FT. R.K.B.
12. PERFORATED SECOND STAGE DAKOTA WITH 1 SHOT PER FT. 6982-6990, 6992-6998, 7046-7056. SAND WATER FRAC PERFORATIONS WITH 27,000# SAND, 1,000# GLASS BEADS, AND 55,440 GALLONS OF 1% KCL WATER.
13. RAN TUBING AND DRILLED OUT BRIDGE PLUG AT 7085 FT. CLEANED OUT TO P.B.T.D. OF 7220 FT. R.K.B.
14. RAN 220 JOINTS OF 1-1/2" E.U.E., 2.90#, JCN-55 TUBING. LANDED AT 7112 FT. R.K.B.
15. WELL COMPLETED 12/16/67.

