

Form 9-731
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 16470

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bengal A

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

South Gallegos-Fr. EXT.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T26N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

1. OIL ☐ WELL GAS ☒ WELL OTHER

2. NAME OF OPERATOR

Dugan Production Corp.

3. ADDRESS OF OPERATOR

P. O. Box 234, Farmington, New Mexico 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850' FNL, 1850' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5997' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work).*

3-25-73

Move in and rig up Lee Wilson Drilling Company rig. Spudded at 10:00 a.m. Drilled 6-3/4" hole with air, hit blow sand at 10', unable to drill below 40' because of blow sand sloughing. Unable to drill with water because of blow sand.

3-26-73

Drilled 6-3/4" hole to 80' with mud. Ran 3 jts. 5 1/2" O.D. 15.5# J-55 8R ST&C casing set at 80' GR, cemented with 35 sacks Class "A" 2% CaCl. P.O.B. 4:00 p.m. 3-26-73. Good cement to surface.



MAR 29 1973

18. I hereby certify that the foregoing is true and correct
Original signed by T. A. Dugan

SIGNED

Thomas A. Dugan

TITLE

Engineer

DATE

3-27-73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side