

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42 R1424.
5. LEASE DESIGNATION AND SERIAL NO.

Tr. 109(NCO-C-14-20-4157)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo Tribe

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Navajo 1-5

9. WELL NO.

1-5

10. FIELD AND POOL, OR WILDCAT

Wildcat-Beau. Mtn. Area

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 5-T26N-R19W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5937 Grd; 5948 KB

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Status Report-1

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Status Report No. 1

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud April 27, 1975 - TD 6087 feet 5/20/1975

17 1/4" hole - 13 3/8" 48# csg - 64 feet cemented 130 sx Class "B" plus 2% CaCl

12 1/4" hole - 8 5/8" 24# csg - 1421 feet cemented w/725 sx Class "B" plus 2% CaCl

7 7/8" hole - 4 1/2" 10 1/2# csg - 6076 feet cemented w/380 sx 50-50 pozmix plus 2% gel

DST No. 1 (Straddle Packer Test - "Barker Creek" Zone) Present depth 5884'

Interval 5640-5719 Open 30 min, fair blow, slid approx 16', had to put on another joint & close tool, opened tool with good blow, slid an additional 5 feet to bottom. Had a good blow throughout, shut-in 60 min. opened 60 min. GTS in 90 min (flammable) TSTM-Shut-in 90 min. Rec. 1050' GCM, 950' GCSW. Bottom packers not holding. IHP-2751 psig, FHP-2743 psig IFP (1) 613 psig EFP (1) 706 psig IFP (2) 777 psig, EFP (2) 914 psig ISIP (1) 2722 psig, FSIP (2) 2716 psig Temp. 146°F

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert E. Lauth

TITLE

Agent-Geological Consultant

DATE

6-5-75

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: