

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0559973

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Grigsby Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

WAW Pictured Cliff Ext.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 9, T26N, R13W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

1. OIL ☐ GAS ☒ OTHER

2. NAME OF OPERATOR

Dietrich Exploration Company

3. ADDRESS OF OPERATOR

602 Midland Savings Bldg., 444 17th St., Denver, CO 80202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

980' FNL & 1350' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6263

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 4½" 10.5# casing to 1464 feet. Cemented with 160 sacks with good circulation, cement circulated. Perforated Pictured Cliff 1404-1410 and sand-water fractured with 10000# 20-40 sand. Swabed 2½ days, recovered 100 barrels of 285 barrel load water. Gas rate too small to measure.

Oral plug instructions per Phil McGrath as Follows:

Squeeze perforations 1404-1410 with 15 sacks class "B" cement and leave cement at 1300 feet.
15 sacks class "B" cement plug 200-400 feet
5 sacks class "B" cement at surface

Cut off pipe 4 feet below ground, spot plug, no dry hole marker. Location will be cleaned, pits filled and area restored to U.S.G.S. specifications.

18. I hereby certify that the foregoing is true and correct

SIGNED

John Alexander
John Alexander

TITLE

Petroleum Engineer

DATE

12-17-76

(This space for Federal or State office use)

APPROVED BY


TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Alfred

*See Instructions on Reverse Side



RECEIVED

DEC 22 1976

U. S. GEOLOGICAL SURVEY
FARMINGTON, N.M.