

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-045-22789

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.
LG 2062

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well
OIL WELL GAS WELL OTHER: _____

2. Name of Operator
Central Resources, Inc.

3. Address of Operator
P.O. Box 2810, Farmington, New Mexico 87499

4. Well Location
Unit Letter C : 790 Feet from the North Line and 1450 Feet from The West Line
Section 32 Township 26N Range 12W NMPM San Juan County

7. Lease Name or Unit Agreement Name
NTB State

8. Well No. 1

9. Hole Name or Wildcat
WAW Fruitland PC

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
6107' GLE

RECEIVED
SEP 15 1998
OIL CON. DIV.
DIST. 2

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO :		SUBSEQUENT REPORT OF :	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: _____ <input type="checkbox"/>	

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Central Resources, Inc. plans to plug and abandon the subject well as follows:
- 1) Plug will be set from the bottom perforation (1117') to the surface (36.3 cuft) by mixing and pumping 33 sks (38.0 cuft) of Class B neat cement.
 - 2) After cement has set up, tag top and refill hole, if necessary.
 - 3) Cut off wellhead and install a regulation dry hole marker.
 - 4) Rehabilitate location as per NMOCD regulations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Gregory E. McIntosh TITLE Production Engineer DATE 9/1/98

TYPE OR PRINT NAME Gregory E. McIntosh TELEPHONE NO. (505)326-3325

(This space for State Use)
APPROVED BY ORIGINAL SIGNED BY CHARLIE T. PERRIN TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 43 DATE SEP 13 1998

CONDITIONS OF APPROVAL, IF ANY: