

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 49-21424.

5. LEASE DESIGNATION AND SERIAL NO.

USA-NM-029144

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
MESA PETROLEUM CO.
3. ADDRESS OF OPERATOR

P. O. BOX 2009, AMARILLO, TEXAS, 79189
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1940' FNL & 1770' FWL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal

9. WELL NO.

#16A

10. FIELD AND POOL, OR WILDCAT

Blanco MV, Otero Chacra

11. SEC., T. R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T27N, R8W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6006' GL

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Commence Drilling Operations

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well 7:00 P.M. on 7/21/78. Drilled 12 1/2" hole to 208'. Ran 8 5/8" 20# csg., set @ 186' KB w/guide shoe, 3 centralizers & baffle. Cmt'd w/115 sxs "B", 2% Cacl. Circulated 25 sxs, PD @ 2:00 A.M. 7/22/78. Drilled 7 7/8" hole to 4775' T.D. Ran 4 1/2" 10.5# K-55 csg., set @ 4775'. Cmt'd w/400 sxs 50-50 Pozmix w/2% Cacl, 6 1/2# gilsonite, 1/2# Halad 9. Had full returns, floats held OK. Dropped bomb & opened DV tool, circ'd 4 hrs., Cmt'd w/465 sxs Howco Lite w/12 1/2% gilsonite, 2% Cacl & 100 sxs "B" w/2% Cacl. Had full returns, plug held OK, job complete @ 2:30 P.M. 7/29/78. Released rig @ 3:00 P.M. 7/29/78.

Presently - waiting on completion unit.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE

Staff Engineer

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

