UNITED STATES

UNITED STATES	5. LEASE 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
decida.	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME.
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1 pil C gas Cv	Dome Federal 25-26-13 25-29. WELL NO. 25-26-13
well well other	1
2. NAME OF OPERATOR Dome Petroleum Corp	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 501 Ariport Drive	NIPP Pictured Cliffs
Suite 107, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
halow)	Sec 25, T26N, R13W
AT SURFACE: 1450 FNL 1190 FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO 용답하는 - 요. 종분수당
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	<u>illia e di la l</u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DIE KOD, AND NO)
	6129' KDB
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	사용 기계
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone
REPAIR WELL	change on-Form 9-330.)
PULL OR ALTER CASING U	원일하다 그 원일출판 원
MULTIPLE COMPLETE	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
ABANDON*	
(other) Spud & set surface casing	
and give pertinent dates.	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent details, and give subsurface locations and including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and including estimated date of starting any proposed work.	
measured and true vertical depths for all markers due assets	
Spud 124" hole at 12 noon 2/5/79. Drilled to 45'. Ran 1 joint (42')	
Spud 12%" hole at 12 hoof 2/3/73. Difficult to 12 hole at 12 hoof 2/3/73. Spud 12%" hole at 12 hoof 2/3/73. Cement with 35 sacks Class B 7", 20#, K55, R3, ST&C casing at 43' GL. Cement with 35 sacks Class B	
7", 20#, K55, R3, ST&C cashing at 45 di. canale nate Cement.	
with 3% CaCl. Plug down at 5:30 pm 2/5/79. Circulate Cement.	
	The state of the s
	CENEY ASSESSED
, se	- Day Yang Ying Day Ting State State Civil
	MINEY !
<i>k</i>	action Summer of the second se
,	
Subsurface Safety Valve: Manu. and Type	Set @
18. I hereby certify that the foregoing is true and correct	
Production Superintendant February 13, 1979	
(This space for Federal or State office use)	
	DATE
APPROVED BY TITLE	
CONDITIONS OF APPROVAL, IF ANY:	er e