

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒  
well well other

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 208, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1450' FNL - 1450' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) surface csg and csg

5. LEASE

NM-61

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Chaco Plant

9. WELL NO.

#36

10. FIELD OR WILDCAT NAME

WAW Fruitland PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 36 T26N R12W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6215' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8-2-79. Moved in and rigged up Morrow Drllg. Co. Spudded 7-3/4" hole. Drilled to 30'. Ran 1 jt 5-1/2" OD 14# "B" condition csg TE 29.50' set @ 29'. Cemented to surface w/7 sx cement.

Ran Welex log to TD. Ran 46 jts 2-7/8" OD 6.4# CW-55 10R reg tbg for csg. TE 1338.97' set @ 1337' GR. Had good circulation and reciprocated pipe while cementing. Preflushed hole w/100 gals. CW-7 mud wash. Cemented w/50 sx 65-35 poz w/12% gel w/1/4# cello flake per sx followed by 50 sx neat w/4% gel w/1/4# cello flake per sx. Circulated 8 bbls cement. Bumped plug w/2000 psi. Released to 750 psi. Shut in. POB 3:15 p.m. 8-6-79.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE Agent

DATE

8-13-79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

7/4/80

