r_n=1	Form Approv é d. Bubyyt Buyyeu 19 - 41 (4 1 tok.)
	ELLEAVE
en e	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2 2 2 2 3 7 3 . 12 3 7 3 7 3 7 3 7 3 7 3 7 3 7 3 7 3 7 3	DAVAJO
SINT THOUGHTS AND REPORTS OF WILLS	7. UNIT AGREEMENT NAME
 not usy this form for proposals to drill or to deepen or plug back to a different consist the form 9-23147 through proposals. 	8. FARM OR LEASE NAME
1. c = gas	DOME_NAVAJO_13-26-13
wes — wes — other	9. WELL NO.
2. NAME OF OPERATOR	1
DOME PETROLEUM CLARCIMIECT	10. FIELD OR WILDOAT NAME
1. ADDRESS OF CREEZERS 501 Airport Drive	MAN ERGITEDOM-BICIURED CTI.:
Suite 107, Farmington, New Mexico 87401	11. SEC., T., R., M., GRIBLK, AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 15001 max 11001 mm	Sec. 13, T26N, R13W
AT SURFACE: 1520' PSL, 1120' PEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	SAN_JUAN NEW MENICO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	5987' GR
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
TULTIPLE COMPLETE	<u> </u>
CHANGE ZONES	
ABANDON=	
(other) REVISIONS TO APD	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertined	lirectionally drilled, give subsurface locations and
1. Install 6" 900 series Double Ram BOP. Tes	st before drilling out from under
surface pipe. Test pipe rams daily and te	
	-
2. Drill 7 7/8" surface hole to 90'. Run 90	of the 15 th vitting
2. Drill 7 7/8" surface hole to 90'. Run 90' casing. Cement with 75 sacks class "B" ce	
cement.	Titil 28 CaCi. Circulate
RECEIVE OCT 04 197	EU
ALOZ.	. \
) not 04 191	/9 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
\ . 001 °	and the second s
U. S. GEOLOGICAL	SURVE
U. S. GEOLOGICAL FARMINGTON.	Y. W.
Subsurface Safety Valve: Manu. and Type	Set @F
18. Thereby certify that the foregoing is true and correct	361, w
DRIG & DROD FO	DREMAN OCTOBER 2, 1979
SIGNED H. D. HOLLANGSHUETH	DATE OCTOBER 2, 1979
This space for Federal or State of	fice use:

*See Instructions on Reverse Side

____TITLE ______ DATE _____

