

no well file

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

John H. Hill and Gordon L. Llewellyn

3. ADDRESS OF OPERATOR Suite 140 Campbell Centre
8350 N. Central Expressway Dallas, Tx 75206

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 895' FNL, 895' FEL Sec. 8
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☒
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE

SF-078384

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newsom B

9. WELL NO.

18

10. FIELD OR WILDCAT NAME

Ballard Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

NE/4 Sec. 8 T-26N R-8W NMPM

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6291' GL 6301' KB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 11" hole @ 7 PM 12-29-79, drilled to 170', ran 4 jts used 7 5/8" 29.7# N-80 LT&C casing, set @ 170' KB. Cemented w/140 sks Class B, 1/4# flocele/sk and 3% CaCl. PD @ 3:45 AM 12-30-79, cement circulated. WOC 12 hrs, tested casing and BOP to 1000# for 15 min, held OK.

Drilled 6 3/4" hole to 2350', ran IES log. Ran new 2 7/8" EUE 6.5# J-55 casing, set @ 2340', cemented w/125 sks 65-35 posmix, 12% gel, 6 1/4# gilsonite/sk and 125 sks 50-50 posmix, 6 1/4# gilsonite and 6# salt/sk. PD @ 6 AM 1-2-80. Approximate top of cement 850'. WOC.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Superintendent

DATE

1-7-80

(This space for Federal or State office use)


APPROVED BY

V. W. Reddick

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:



ACCEPTED FOR RECORD

JAN 15 '80

FARMINGTON DISTRICT

*See Instructions on Reverse Side

NMOCC