-

- partie (st

Form Approved. Budget Bureau No. 42-R1424

5. LEASE

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY		NM-03153
		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
		- <u> </u>
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
		O.H. Randel
1. oil gas well other		9. WELL NO. 3444 2 2 4 4 4 4 4 4 4 4 4 4 4 4 4 4 4
2. NAME OF OPERATOR Energy Reserves Group, In	nc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR		Basin Dakota
P.O. Box 3280 - Casper, Wyoming 82602		11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1,700' FSL & 1,800' FEL (NW/SE) AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		Sec. 10-T26N-R11W
		12. COUNTY OR PARISH 13. STATE
		14. API NO.
		15. ELEVATIONS (SHOW DF, KDB, AND WD)
		G.L. 6,364' KB 6,378'
	SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	RECE	
REPAIR WELL		(NOTE: Report results of multiple completion or zone change on Form 9–330.)
PULL OR ALTER CASING	H APK 1	U 1000 change on Form 9-330.)
MULTIPLE COMPLETE CHANGE ZONES	☐ US GEOLO	GICAL SURVEY
ABANDON*	FARMING	TON, N. M
(other)	I	
17. DESCRIBE PROPOSED OR COMPLE including estimated date of starting measured and true vertical depths f	TED OPERATIONS (Clearly stage any proposed work. If well is or all markers and zones pertine	te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)*
The above referenced we	11 was spudded @ 7:30	O P.M. 4-5-80 살림() - 현 등 등 등
		9 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
Drilled 12-1/4" hole to 950		
Ran 22 jts - 8-5/8" 0.D	1., 24#, K-55, 8Rth, 1	R-3, SS, New casing set @ 944' (K.B.)
Cemented w/665 sx of Class B" cement w/2% Carreturns. Plug down @ 1:15 P.M. 4-6-80.		act ₂ a 1/4# verification door cement
returns. Flug down e 1.	15 7 4 0 00.	
Nippled up and pressure tested B.O.P.E. to 1000 psi		1000 psi heidok 1980
4-7-80: Drilling 7-7/8" hole @ 1,312'.		OF DIST 3
Subsurface Safety Valve: Manu. and Typ	e	Ft.
18. I hereby certify that the foregoing is true and correct		
SIGNED Rose C. G. illespiritle Dr. 1g Supt.		DATEApril 8, 1980
SIGNED 11 A STATE OF THE STATE	(This space for Federal or State of	
ARROOVED BY	TITLE	LGGERFED-FUETEGORD-
APPROVED BY		200
NMOC C		######################################
	MIMICOR	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
		토로 ニ로 그 그 그 그 그 보다.

*See Instructions on Reverse Side