

1973

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☐ other ☐ DRY HOLE

2. NAME OF OPERATOR

DOMO PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR 501 Airport Drive  
Suite 107, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1650' FSL, 990' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

FED 100

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PLUGGED AND ABANDONED WELL AS FOLLOWS:

PLUG NO.	INTERVAL	FEET	SACKS CEMENT
1	1050' - 1300'	250'	50
2	0' - 200'	200'	50

Cut surface casing off 4' below GL & backfilled. Cleaned location and fenced pit. Pit will be backfilled when dry and location will be reseeded according to U.S.G.S. specifications.

**RECEIVED**

MAY 11 1984

Subsurface Safety Valve: Manu. and Type

OIL CON. DIV.

18. I hereby certify that the foregoing is true and correct

DIST. 3

SIGNED

H. D. HOLLINGSWORTH

TITLE DRLG & PROD FOREMAN

DATE February 8, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NM000

MAY 10 1984

RECORD

BY

A

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☐ other ☒ DRY HOLE
2. NAME OF OPERATOR  
DOMO PETROLEUM CORPORATION
3. ADDRESS OF OPERATOR 501 Airport Drive  
Suite 107, Farmington, NM 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL, 990' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

## SUBSEQUENT REPORT OF:

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

FEB 12 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

PLUGGED AND ABANDONED WELL AS FOLLOWS:

PLUG NO.	INTERVAL	FEET	SACKS CEMENT
1	1050'-1300'	250'	50
2	0' - 200'	200'	50

Cut surface casing off 4' below GL & backfilled. Cleaned location and fenced pit. Pit will be backfilled when dry and location will be reseeded according to U.S.G.S. specifications.

RECEIVED

DEC 21 1984

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED H. D. HOLLINGSWORTH TITLE DRILL & PROD FOREMAN DATE February 8, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

OIL CON. DIV.  
DIST. 3APPROVED  
AS AMENDED

DEC 18 1984

M. MILLENBACH  
AREA MANAGER

Approved as to plugging of the well here. Liability under bond is retained until surface restoration is completed.

Instructions on Reverse Side