Form 3160-5 (December 1989)

Approved by

Conditions of approval, if any:

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

PORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

Expires: September 30, 1990

5. Lease Designation and Serial No.

SF079679

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottes or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA. Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well X Gas Well 8. Well Name and No. 2. Name of Operator Gallegos Federal 26-11-17 #1 9. API Well No. Maralex Resources, Inc. 3. Address and Telephone No. P. O. Box 421, Blanco, NM 87412-0421 (505) 325-5599 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State 920' FNL & 990' FEL NE/NE Section 17, T26N, R11W San Juan County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Change of Plans Recompletion **New Construction** Non-Routine Fracturing Subsequent Report Plugging Back Water Shut-Off JAN2 3 1993 Casing Repair Final Abandonment Notice Altering Casing Conversion to Injection Production Casing OIL CON. DIV. (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* TD @ 1625' on 1-06-93 Production Casing: 6 1/4" Hole Size: 38 Jts (1603.8') 4 1/2", 10.5#, J-55, Casing set @ Casing: 1609' KB, Guide Shoe @ 1608', Float Collar @ 1594' 10 Centralizers @ 1589', 1547', 1463', 1379', 1295', 1211', 1127', 1034', 959', & 875'. Cement: 120 sx Class B w/2% Meta-Silicate & 1/4 pps Celo-Flake (2.06 Yield/247 cu ft) + 75 sx Class B w/2% CaCl & 1/4 pps Celo-Flake (1.19 Yield/89 cu ft). Circ 6 bbls cement to surface. Bump Plug w/1000 osi. Plug Down @ 9:30 PM on 1-06-93. 14. I hereby certify that the foregoing is true and correct (915) 694-6107. 1/09/93 Camua. Title (This space for Federal or State office use) ACCEPTED FOR RECORE

·Sea incompation on Daviges Side

NMOCD