

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well

GAS

2. Name of Operator

MERIDIAN OIL

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1650' FNL, 990' FEL, Sec. 30, T-28-N, R-4-W, NMPM

5. Lease Number

NM-03862

6. If Indian, All. or Tribe Name

7. Unit Agreement Name

San Juan 28-4 Unit

8. Well Name & Number

San Juan 28-4 U #16

9. API Well No.

30-039-07327

10. Field and Pool

Blanco Mesaverde

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action


☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations

- 7-14-95 MIRU. ND WH. NU BOP. PT BOP. TOOH w/208 jts 2 3/8" tbg. TIH w/5 1/2" gauge ring to 6350'. POOH. TIH w/5 1/2" cmt retainer, set @ 6308'. PT tbg to 1000 psi, OK Establish injection into Mesaverde perfs. Plug #1: pump 64 sx Class "B" cmt below cmt retainer into perfs, 39 sx Class "B" cmt on top of cmt retainer, TOC @ 5964'. TOOH to 5425'. SDON.
- 7-17-95 TOOH to 4541'. Load hole w/183 bbl wtr. PT csg to 500 psi, failed. Plug #2: pump 97 sx Class "B" cmt inside 5 1/2" lnr @ 3964-4541'. TOOH. TIH w/7 5/8" gauge ring to 3800'. TOOH. TIH, perf 3 sqz holes @ 3852'. TOOH. TIH w/7 5/8" cmt retainer, set @ 3785'. TOOH. Establish injection. Plug #3: pump 96 sx Class "B" cmt below cmt retainer outside 5 1/2" csg, 54 sx Class "B" cmt on top of cmt retainer, TOC @ 3544'. TOOH. SDON.
- 7-18-95 Load hole w/32 bbl wtr. Attempt to PT, failed. Perf 3 sqz holes @ 2450'. TOOH. TIH w/7 5/8" cmt retainer, set @ 2397'. Establish injection. Attempt to PT csg, failed. Plug #4: pump 44 sx Class "B" cmt below cmt retainer outside 7 5/8" csg @ 2350-2450', 22 sx Class "B" cmt on top of cmt retainer, TOC @ 2299'. TOOH. TIH, perf 3 sqz holes @ 342'. TOOH. Establish circ out bradenhead w/8 bbl wtr. Plug #5: pump 166 sx Class "B" cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. ND BOP. Cut off WH. Pump 5 sx Class "B" cmt to fill 7 5/8" csg. Install dry hole marker w/15 sx Class "B" cmt. RD. Rig released. Well plugged and abandoned 7-18-95.

14. I hereby certify that the foregoing is true and correct.

Signed

 Title Regulatory Administrator Date 7/27/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Date

APPROVED

1995

DISTRICT MANAGER