

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon.

As far as can be determined from all available records

Signed W. R. Brown

Location of well in Township 16 N. of Range 17 E. of 11th Meridian
Section 36 Township 16 N. Range 17 E. Meridian
County Rock State Ark.

Location of well in Township 16 N. of Range 17 E. of 11th Meridian
Section 36 Township 16 N. Range 17 E. Meridian
County Rock State Ark.

Company Rockwell Drilling Co.

OIL OR GAS SANDS OF ZONES

Q: ad can store?

April 10, 1955, Total depth 4740', (retainer at 4395') with 12,600 gallons #6 diesel oil & 12,300 fine-grain sand. Breakdown pressure 1600 psi, maximum pressure 1900 psi, injection rate 7.9 bbls./min. Natural gas 55 MCF/D.

April 20, 1955, Total depth 4700', (retainer at 4374') with 13,200 gallons oil & 15,000 # sand. Breakdown pressure 0 psi. Injection rate 7.9 bbls./min. Maximum pressure 1900 psi, minimum pressure 1600 psi. Flow with 3600 gallons. Natural gas 55 MCF/D.

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of reworking, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

HISTORY OF OIL OR GAS WELL

U. S. GOVERNMENT PRINTING OFFICE 16-43084-2

[illegible]