

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR  
BOX 289, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1540'S, 1800'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE  
SF 080505A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME  
San Juan 28-6 Unit

8. FARM OR LEASE NAME  
San Juan 28-6 Unit

9. WELL NO.  
56A

10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec: 11, T-28-N, R-6-W  
NMPM

12. COUNTY OR PARISH | 13. STATE  
Rio Arriba | New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6529 GL

REQUEST FOR APPROVAL TO:      SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF      

FRACTURE TREAT      

SHOOT OR ACIDIZE      

REPAIR WELL      

PULL OR ALTER CASING      

MULTIPLE COMPLETE      

CHANGE ZONES      

ABANDON\*      

(other)      

RECEIVED

(NOTE: Report results of multiple completion or zone on Form 9-330.)

JAN 29 1979

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/11/78: T.D. 3795'. Ran 92 joints 7", 20#, K-55 intermediate casing, 3782' set at 3795'. Cemented with 257 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement 2250'.

12/14/78: TD 6060'. Ran 75 joints 4 1/2", 10.5#, K-55 casing liner, 2434' set 3626-6060'. Float collar set at 6045'. Cemented with 424 cu. ft. cement. WOC 18 hours.

1/11/79: PBSD 6045'. Tested casing to 3500#, OK. Perfed 5171, 5187, 5214, 5224, 5244, 5250, 5256, 5305, 5314, 5319, 5332, 5337, 5350, 5356, 5360, 5369, 5442, 5460, 5477, 5482, 5525, 5529 with 1 SPZ. Fraced w/70,000# 20/40 sand and 140,000 gal. water. Flushed w/7140 gal. water. Perfed 5600, 5608, 5612, 5619, 5626, 5638, 5659, 5665, 5675, 568', 5700, 5705, 5714, 5718, 5737, 5758, 5788, 5807, 5831, 5858, 5865, 5933, 5970, 6015w/1SPZ.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft. (OVER)

18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Brisco TITLE Drilling Clerk DATE 1/24

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
JAN 29 1979  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.

### Instructions

**General:** This form is designed for submitting proposals to perform certain well operations; and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

**Item 4:** If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

**Item 17:** Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

Fraced w/75,000# 20/40 sand and 145,000 gal. water.  
Flushed w/7500 gal. water.