



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. SE 000168

Unit \_\_\_\_\_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 26, 1961

**E. O. Watson 13"**  
Well No. 1 is located 790 ft. from [N] line and 790 ft. from [E] line of sec. 21  
NE 1/4 Section 21 27 N 12 W N.W.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Basin Dakota San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the ground level ~~surface~~ above sea level is 5822 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Running and cementing surface casing as follows: Run 1 joint casing, 9-5/8" OD, 40#, J-55, 24', and 6 joints casing, 8-3/8" OD, 24#, J-55, 24'. Casing set at 209'. Cemented with 160 sacks cement, 24 #100. Plug down 1:30 p.m. 7-1-61. WOC 12 hours. Pressure tested casing to 800 pounds for 30 minutes. Pressure held o.k.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Tenneco Oil Company

Address P. O. Box 1714

Durango, Colorado

By L. B. Fluh

Title District Production Superintendent