NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122
Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Basin Dakota Formation Dakota County San Juan

Initial X Annual ____ Special ____ Date of Test 8-27-64

Company PAN AMERICAN PETROLEUM CORP. Lease H. B. McGrady "A" Well No. 1

Unit L Sec. 14 Twp. 27N Rge. 12W Purchaser ____

Casing 4-1/2 Wt. 10.5 I.D. 4.052 Set at 6274 Perf. 6150-68 6200-16 To 6114-28

Tubing 2-3/8 Wt. 4.7 I.D. 1.995 Set at 6161 Perf. 6104 To 6110

Gas Pay: From 6114 To 6216 L 6165 xG .700 -GL 4316 Bar.Press. 12

Producing Thru: Casing ____ Tubing X Type Well Single
Single-Bradenhead-G. G. or G.O. Dual

Date of Completion: 8-20-64 Packer None Reservoir Temp. ____

OBSERVED DATA

Tested Through [illegible] (Choke) [illegible] Type Taps ____

No.	Flow Data: [illegible] (Line) Size	Flow Data: (Choke) (Orifice) Size	Flow Data: Press. psig	Flow Data: Diff. h_w	Flow Data: Temp. °F.	Tubing Data: Press. psig	Tubing Data: Temp. °F.	Casing Data: Press. psig	Casing Data: Temp. °F.	Duration of Flow Hr.
SI	7 Day					2039		2050		
1.	1 Inch	.750	619			619	60° est.	1288	60° est.	3 Hr.
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_w p_f}$	Pressure psia	Flow Temp. Factor F_t	Gravity Factor F_g	Compress. Factor F_{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	12.3650		631	1.0000	.9130	1.001	7615
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio ____ cf/bbl.
Gravity of Liquid Hydrocarbons ____ deg.
F_c ____ $(1-e^{-s})$ ____

Specific Gravity Separator Gas ____
Specific Gravity Flowing Fluid ____
P_c 2051 P_c^2 4,206,601

No.	P_w / P_t (psia)	P_t^2	F_cQ	$(F_cQ)^2$	$(F_cQ)^2$ $(1-e^{-s})$	P_w^2	$P_c^2-P_w^2$	Cal. P_w	$\frac{P_w}{P_c}$
1.						1,680,000	2,516,601		
2.									
3.									
4.									
5.									

Absolute Potential: 11,447 MCFPD; n .75

COMPANY PAN AMERICAN PETROLEUM CORPORATION
ADDRESS Box 480, Farmington, New Mexico
AGENT and TITLE E. L. Mahone, District Engineer
WITNESSED By: ORIGINAL SIGNED BY F. W. Foell
COMPANY ____

REMARKS

ORIGINAL SIGNED BY F. W. Foell

RECEIVED
SEP [illegible] 1964
OIL CON. COM.
DIST. 3

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 60° F.

P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia

P_w = Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia

P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia

P_f = Meter pressure, psia.

h_w = Differential meter pressure, inches water.

F_g = Gravity correction factor.

F_t = Flowing temperature correction factor.

F_{pv} = Supercompressability factor.

n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t.