

Santa Fe

078099

Ginther

DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND SURVEY

Unit

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER PRODUCTION
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF ABANDONMENT
	SUPPLEMENTARY WELL HISTORY
	<b>Subsequent Report of Sandfrac Treatment</b> <input checked="" type="checkbox"/>

INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA

July 22nd, 1959

Well No. 1 is located 790 ft. from ☒ N line and 790 ft. from ☒ W line of sec. 13

NE/4 NE/4 Sec. 13

(1/4 Sec. and 1/4 Sec. N.E.)

27N

(Twp.)

13W

(Range)

N.M.P.M.

(Meridian)

Wildcat

(Name)

San Juan

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 5828 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding, cementing points, and all other important proposed work)

- 4-30-59 TD 6018' RKB. Cleaned out to 6010'. Perforated 5992-6002' with 4 shots per foot. Sandfraced with 78,708 gallons water and 60,000# sand, flushed with 7,308 gallons water. Breakdown pressure with one truck 2600#, broke to 2000#. Treating pressure maximum 4100#, minimum 3800#, average injection rate 58 barrels per minute. Set bridge plug at 5960'.
- 5- 5-59 Perforated 5915-35' with 4 shots per foot. Sandfraced with 94,080 gallons water and 96,500# sand, flushed with 10,908 gallons water. Maximum pressure 4500#, minimum 3800#, average treating pressure 4000#, average injection rate 58 barrels per minute.

(continued)

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company

Address

By

Page #1

Title




(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 078099  
Unit Ginther

Page #2

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<b>Subsequent Report of Sandfrac Treatment</b> <b>x</b>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 22nd, 19 59


Well No. \_\_\_\_\_ is located \_\_\_\_\_ ft. from  $\left\{ \begin{matrix} N \\ S \end{matrix} \right\}$  line and \_\_\_\_\_ ft. from  $\left\{ \begin{matrix} E \\ W \end{matrix} \right\}$  line of sec. \_\_\_\_\_

\_\_\_\_\_ (1/4 Sec. and Sec. No.) \_\_\_\_\_ (Twp.) \_\_\_\_\_ (Range) \_\_\_\_\_ (Meridian)  
\_\_\_\_\_ (Field) \_\_\_\_\_ (County or Subdivision) \_\_\_\_\_ (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging points, and all other important proposed work)



5- 6-59 Set bridge plug at 5908'. Perforated 5895-5904' with 4 shots per foot. Established communication with lower zone. Ran Guiberson Type WME magnesium plug set at 5880'. Perforated 5862-72' with 4 shots per foot. Sandfraced with 78,750 gallons water and 60,000# sand, flushed with 6,270 gallons water. Maximum pressure 4900#, minimum 3700#, average injection rate 51 barrels per minute. Final pressure on casing 2000#, decreasing in 3 minutes to 1680#.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company BENSON-MONTIN-GREER DRILLING CORP.  
Address 158 Petroleum Center Building  
Farmington, New Mexico  
By [Signature]  
Title Vice-President

