

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports on Wells

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

October 27, 1950 - Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Stanolind Oil and Gas Company **Bruce Sullivan** Well No. **1** in the
Company or Operator Lease

SW/4 of NE/4 of Sec. **11**, T. **27-N**, R. **10-W**, N. M. P. M.,
Kutz Canyon Field **San Juan** County.

The dates of this work were as follows: **October 26, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **October 25** 19 **50**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On October 26, 1950 at 4:00 A. M., 36 hours had elapsed since cementing the 8-5/8" casing at 114' with 100 sacks cement. Cement circulated to surface.

At that time pipe was tested with 300 psi. Pressure after 30 minutes was 300 psi. Approximately 30' of solid cement was drilled in bottom of pipe and water shut-off tested with 400 psi. Pressure (over)

Witnessed by **H. W. Herndon - Stanolind Oil and Gas Company - Prod. Foreman**
Name Company Title

Subscribed and sworn before me this **27th**

day of **October**, 19 **50**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **H. C. L. Knight Jr.**

Position **Field Engineer**

Representing **Stanolind Oil and Gas Company**
Company or Operator

My commission expires **2-23-54**

Address **Box "F"; Hobbs, New Mexico**

Remarks:

APPROVED
10-30-50

Oil and Gas Inspector Dist. #7

Title

was 400 psi after 30 minutes.

Tests were considered satisfactory and drilling has been resumed.

--	--	--	--