Form 9-331 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office Santa Fo	
Lease No. F-077382	
Unit USA Hargrave	H 186

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.	
IOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
IOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
	U. A. GLULDGICAL SURVE
(INDICATE ABOVE BY CHECK MAR	RENATURE OF REPORT, NOTICE, OR OTHER DATA MINGELL MEW MENT
lis Hargrave "H"	Farmington, New Mexico August 25 19 59
UNI 1 is leasted 780 ft from	[N] line and 1850 ft. from $[E]$ line of sec. 9
(4 Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
monte Peak Sakota San Ji	van Hew Yexico
(Field) (Count	y or Subdivision) (State or Territory)
ate names of and expected depths to objective sands; show a ing points, and al	
ing points, and all productions of and expected depths to objective sands; show ing points, and all producted in the sands; show ing points, and all producted in the sands; show ing points and all productions in the sands; show it is a sands in the sands; show it is a sands in the sands; show it is a sands in the sands; show it is a sands; show	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- il other important proposed work) 13, 1959, and drilled to 365 (cet. 8-5/8 in a section of cenent containing 2% calcium chlor
Spunded 12-1/4 inch hole on August casing was set at 34 feet with 32 Coment circulated. After waiting	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ill other important proposed work) 13, 1959, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test heald with no indication of aressure drop.
Spudded 12-1/4 inch hole on August casing was set at 34 feet with 22 Commit circulated. After waiting	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ill other important proposed work) 13, 1959, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test heald with no indication of aressure drop.
Spunded 12-1/4 inch hole on August casing was set at 34 feet with 32 Coment circulated. After waiting	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ill other important proposed work) 13, 1959, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test heald with no indication of aressure drop.
Spudded 12-1/4 inch hole on August Casing was set at 34 feet with 22 Coment circulated. After waiting	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ill other important proposed work) 13, 1959, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test heald with no indication of aressure drop.
Spudied 12-1/4 inch hole on August casing was set at 34 feet with 22 count circulated. After waiting with 1050 psi for 30 minutes, which deduced hole to 7-7/8 inch at 365	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ill other important proposed work) 13, 1957, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test h held with no indication of pressure drop. feet and resumed drilling containing. OIL COPA COMM. DIST. 3
Spudded 12-1/4 inch hole on August casing was set at 34 feet with 32 Coment circulated. After waiting with 1050 ai for 30 minutes, which addressed hole to 7-7/8 inch at 365	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ll other important proposed work) 13, 1957, and drilled to 365 (set. 8-5/6 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test held with no indication of arsssure drop. feet and resumed drilling printiples. Oil Contains DIS1.3 Lin writing by the Geological Survey before operations may be commenced.
Spudded 12-1/4 inch hole on August casing was set at 74 feet with 22 count circulated. After waiting with 1050 cai for 30 minutes, which deduced hole to 7-7/8 inch at 365	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement other important proposed work) 13, 1957, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test heald with no indication of aressure drop. 1 cent and resumed drilling containing. OIL COR. COM. DIST. 3 ORIGINAL SIGNED BY
Spudied 12-1/4 inch hole on August casing was set at 34 feet with 32 count circulated. After waiting with 1050 pai for 30 minutes, which deduced hole to 7-7/8 inch at 365	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement other important proposed work) 13, 1957, and drilled to 365 feet. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test held with no indication of arcseure drop. 1 Core commenced. OIL CORE COMMENCED IN THE COMMENCED I
Syndici 12-1/4 inch hole on August casing was set at 34 feet with 22 count circulated. After waiting with 1050 cai for 30 minutes, which address the to 7-7/8 inch at 365	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement other important proposed work) 13, 1957, and drilled to 365 (set. 8-5/8 in 5 sacks of cement containing 2% calcium chlor on cement casing and water shut off were test heald with no indication of aressure drop. 1 and resumed drilling containing 2% calcium chlorous feet and resumed drilling contains. OIL COPY COMMON DIST. 3 ORIGINAL SIGNED BY R. M. Bauer, Jr.