Forma 3-331 a (Feb. 1951)

\*

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land	Offic	. 3	mte l	<u> </u>
Lease	No.	9 <b>7</b> -(	77736	<b>.</b>
Unit .	N,	H.	Galt	<b>#</b> J0

NOTICE OF INTENTION TO DRI	ш	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHA	102 ( 2010	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
	T WATER SHUT-OFFDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ALTERING CASING SUBSEQUENT REPORT OF RE-DRILLING OR FRANK
NOTICE OF INTENTION TO SHO	OOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT U
	L OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
(1)	INDICATE ABOVE BY CHECK MARK NATU	U. S. GEOLOGICAL SURVEY FARMINGTON, NEW MEXICO
M. Galt "J"	7	ermington, New Mexico November 24, 19 59
	<b>700</b> (	* 1: 1750 & from *** line of cos . 4
_	located	${0 \atop 0 \atop$
(½ Sec. and Sec. No.)	(Twp.) (Rang	
polo Pock Dakota (Field)	Sen Juan (County or Sub	West Ke xi. 60 (State or Territory)
	DETAILS	OF WORK
stal depth 65001, lage easent toel a mining 1-1/2 po seing with 3000 po seend stage with 3 th no indication	pins to objective sands; show sizes, we ing points, and all other plug back depth 6461 at 2056'. Comented fixmeds Tuf-Plug per sas which held with no of pressure drop. Go 2056' and released ri	eights, and lengths of proposed casings; indicate mudding jobs, cement-important proposed work)  . 4-1/2" easing was set at 6500" with 2- yet stage with 400 sacks 6% gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Commission. Tosted easing with 3000 pei which held led circulation through out both stages. If on Hovember 17, 1959. Proparing to move
tal depth 69001, age essent tool a mining 1-1/2 point with 3000 point stage with 3 th no indication willed DV tool at	physical properties and a properties of the points and all other plug back depth 6461. The points of the properties of t	eights, and lengths of proposed casings; indicate mudding jobs, cement-important proposed work)  . 4-1/2" easing was set at 6500" with 2- yet stage with 400 sacks 6% gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Commission. Tosted easing with 3000 pei which held led circulation through out both stages. If on Hovember 17, 1959. Proparing to move
stal depth 65001, age essent toel a mining 1-1/2 po sing with 3000 po send stage with 3 th no indication	pins to objective sands; show sizes, we ing points, and all other plug back depth 6461 at 2056'. Comented fixmeds Tuf-Plug per sas which held with no of pressure drop. Go 2056' and released ri	eights, and lengths of proposed casings; indicate mudding jobs, cement-important proposed work)  . 4-1/2" easing was set at 6500" with 2- yet stage with 400 sacks 6% gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Commission. Tosted easing with 3000 pei which held led circulation through out both stages. If on Hovember 17, 1959. Proparing to move
tal depth 69001, age essent tool a mining 1-1/2 point with 3000 point stage with 3 th no indication willed DV tool at	pins to objective sands; show sizes, we ing points, and all other plug back depth 6461 at 2056'. Comented fixmeds Tuf-Plug per sas which held with no of pressure drop. Go 2056' and released ri	eights, and lengths of proposed casings; indicate mudding jobs, cement-important proposed work)  . 4-1/2" easing was set at 6500" with 2- yet stage with 400 sacks 6% gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Commission. Tosted easing with 3000 pei which held led circulation through out both stages. If on Hovember 17, 1959. Proparing to move
tal depth 6500', age essent toel a mtaining 1-1/2 points with 3000 person stage with 2000 p	plug back depth 6161' at 2056'. Comented file punds Tuf-Plug per ses at which held with no of pressure drop. Go 2056' and released ri to comence completie	eights, and lengths of proposed casings; indicate mudding jobs, cement- important proposed work)  . 4-1/2* easing was set at 6500* with 2- yet stage with 400 sacks 65 gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Committed it. Tosted easing with 3000 pet which held led circulation through out both stages. g on November 17, 1959. Preparing to move in operations.
real depth 6500', lage easent tool a meaning 1-1/2 per point with 3000 per point stage with 2000 per point stage with 2000 per	plug back depth 6161' it 2056'. Commission sizes, we impoints, and all other plug back depth 6161' it 2056'. Commission fix must be far-Plug per sassion which held with no 250 sacks 45 gal commission pressure drop. Go 2056' and released rite commission completion	eights, and lengths of proposed casings; indicate mudding jobs, cement- important proposed work)  . 4-1/2* easing was set at 6500* with 2- yet stage with 400 sacks 65 gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Committed it. Tosted easing with 3000 pet which held led circulation through out both stages. g on November 17, 1959. Preparing to move in operations.
real depth 65001, sage easent tool a meaning 1-1/2 per saing with 3000 per sage with 2 to indication willed DV tool at a completion unit	plug back depth 6161' at 2056'. Comented file punds Tuf-Plug per ses at which held with no of pressure drop. Go 2056' and released ri to comence completie	eights, and lengths of proposed casings; indicate mudding jobs, cement- important proposed work)  . 4-1/2* easing was set at 6500* with 2- yet stage with 400 sacks 65 gel sement k, followed by 100 sack neat sement. Toste indication of pressure drop. Committed it. Tosted easing with 3000 pet which held led circulation through out both stages. g on November 17, 1959. Preparing to move in operations.

Atta: L. O. Speer, Jr.

Area Sagimeer

GPG 862040

Title ....