NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Besin	Dakot	<u> </u>	Fc	ormation	Dalo	ota		County_	Set	a Jana	
Initial Annual Annual					Special				Date of	Test_	2-27-65	
omp	any Austr	al 01	l Co.	v • · · · · · · · · · · · · · · · · · ·		Lease	Pederal.	MARSHA	We	ell No.	1-1	- 3
	y s										_	
asi	ng 4 W	/t. 10	.5 I	.D	Se	t at_ 6	682 Pe	rf. 64	19	_To	6634	
	ng 2 1/16 N											
as l	Pay: From_	6419	To	6634	L	x	G .65 es	_GL_		Bar.P	ress	
Producing Thru: Casing						TubingType			Vell_Single			
ate of Completion:				Si Packer			ingle-Bradenhead-G. G. or G.O. Dual Reservoir Temp.					
							ED DATA					
ste	ed Through	(TTO	ver) (Choke)	(Meter)				Type Ta	.ps		
			Flow D				Tubing	Data	Casing			
	(Prover) (Line)	(Ch			Diff.	Temp.		Temp.	Press.		•	Duration of Flow
	Size	1 '	ize	psig	h _w	°F.	psig	°F.	psig	°F∙		Hr.
							2141		21.37			
+		3/	Z#	267		62			984		3	ire.
+												
		L										
T	Coeffici	ent	 	Pr		Flow		Gravity		ess.	Rate	of Flow
•	(24-Hou	(24-Hour) 7/		 of	Fac sia F			Factor F _g	Fact F _{pv}	-		FPD 025 psia
#			Y WII				<u> </u>					
	12.365				279 .998		X .	.9608	1	JU26	3401	
+			 					···				
vit	quid Hydro	d Hydi	rocarbo				ALCU ATI	Speci Speci	fic Grav fic Grav	ity Flo	owing F	luid
1	(pola)		E F	,Q	(F _c Q) ²	(F ₀	Q) ² -e-s)	P _w 2	P _c -P _w		Cal.	Pw Pc
#	9%							992,016	3,643,3	93		1,2723
										 	<u> </u>	
sol	ute Potent:			074		MCFPD;	n = .75	1.1979)	1		
DRE	SS	es 23	OLI C	dagten	, N. M.						 -	
ENT	and TITLE	Origin	al sign	ed by T	A. Dug	an The	as A. Du	gan, Coos	ulting B	nginee		
	NY					DESC	DVC			6	TFIV	TAT
						REMA	ARKS			/KI	LULIY	rn /
										•	AR 151	
										OIL	CON.	
											DIST.	3

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \subseteq Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- Pc= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt_ Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor. .
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.