5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR	NM 03549
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
1 oil gee	8. FARM OR LEASE NAME Florance C
well well other 2. NAME OF OPERATOR	9. WELL NO. #2 (OWWO)
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Box 289, Farmington, New Mexico 87401	Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 20, T-28-N, R-8-W N.M.P.M.
AT SURFACE: 1800'S, 1650'W AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5749 GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
ABANDON*	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	lirectionally drilled, give subsurface locations and
0-26-79: Pulled tubing. cut tubing off @ 3828'. Se w/235 cu. ft. cement. WOC. Perfed squeeze @ 1149'. Cemented w/295 cu. ft. cement. W	hole @ 1230. Cement Retainer s
0-28-79: Set Cement Retainer @ 3608'. Cemented w/23	5 cu. ft. cement WOC.
0-29-79: Drilled side track hole from 3705' to 3723'	. Drilled to total depth of 4807
1-1-79: TD 4807'. Ran 149 joints 4 1/2", 10.5#, K-5. Float collar set at 4790'. Cemented w/ 246	
Top of Cement at 2950.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct SIGNED	rk November 7, 1979
(This space for Federal or State off	fice use)