

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other _____

2. NAME OF OPERATOR
BIXCO, INC

3. ADDRESS OF OPERATOR
P.O.Box 255, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' fN1, 1650' fW1
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Completion			<input checked="" type="checkbox"/>

5. LEASE
NM-33035

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A

7. UNIT AGREEMENT NAME
N/A

8. FARM OR LEASE NAME
Campbell

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
S9- T27N+R13W, NMPM


12. COUNTY OR PARISH
San Juan

13. STATE
N.M.

14. API NO.
30-045-24599

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5957 Gr.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/8/80+Rigged up swabbing unit and ran cement bond log from surf. to T.D. of 1428'. Good bond Ran gamma-ray correlation log 1200' to T.D. Perforated 2 7/8" csg. 1367-73' (IES log measurements) with 2 jet shots per ft. Unloaded water blanket and blew gas. Nippled up and installed wellhead manifold.

12-9-80-Blew well down and gaged 137 MGFPD. SIPC-287# 12/11/80+Ran 42 jts. (1371.08') of 1 1/2", 2.4#, J-55, 10-rnd, EUE tubing, set at 1368'. Installed 2 1/2" x 1 1/2" tubing head and wellhead manifold assembly. Shut in well for 7-day shut in production test. 12/12/80-Filled pits and cleaned and leveled location

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. R. Speer TITLE Agent DATE December 15, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITION ACCEPTED FOR RECORD

DEC 22 1980

NMCCC

*See Instructions on Reverse Side

BY BW FARMINGTON DISTRICT