

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

1000 Petroleum Building -- Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1630' FSL, 1800' FWL (NE/4 SW/4)

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Subsequent report of operations

5. LEASE

SF 078896

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

Federal 29

9. WELL NO.

23

10. FIELD OR WILDCAT NAME

West Kutz P.C.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 29-T27N-R11W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico


14. API NO.

30-045-24768

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6183' GR 6195' KB

(NOTE: Report results of multiple completion or zone change on Form 9-331-C.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 2:30 PM 3-23-81. Drilled 12 1/4" hole to 155' KB. Ran 3 jts, 138.25', 8-5/8", 24#, K55, R3, ST&C casing landed @ 151' KB. Cemented w/110 sx Class "B" regular, 3% CaCl₂, 1 sx flocele. Cement circulated to surface. PD 6:40 PM 3-23-81. WOC 12 hrs.

Drilled 7-7/8" hole to 1955' TD. Ran DIL and CNL/FDC w/GR & Caliper logs. Ran 47 jts, 1928.19', 4 1/2", 10.5#, J55, R3, ST&C casing landed @ 1940' KB. Cemented w/275 sx 65/35 Pozmix, 12% gel, 12 1/2# Gilsonite/sx followed by 100 sx Class "B" regular. Good returns throughout. Cement circulated to surface. PD 4:15 AM. Rig released 5 AM 3-26-81.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm S. Schuman Prod Spt-So. Rks DATE 3-26-81

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE ACCEPTED FOR RECORD

NMOCC

APR 01 1981