

PHONE 334-6191
P. O. BOX "B"



JERRY WAYNE SANDEL
PRESIDENT

AZTEC, NEW MEXICO 87401

HOLE DEVIATION AFFIDAVIT

OPERATOR: Depco, Inc.
WELL NAME: Federal, Well #30-41
DESCRIPTION OF LEASE: 1120' Fr. N. In. and 790' Fr. E In.,
Section 30- Township 27N- R 11W,
San Juan County, New Mexico

<u>FROM</u>	<u>TO</u>	<u>DEVIATION</u>
0'	136'	1/4 °
136'	600'	1/4 °
600'	1127'	1/4 °
1127'	1467'	1/2 °
1467'	1925'	1/2 °

I hereby swear or (affirm) that the statements made or a full and correct report.

AZTEC WELL SERVICING CO.

Jack LeBleu
Jack LeBleu, Toolpusher

SWORN TO AND SUBSCRIBED BEFORE ME by Jack LeBleu, Toolpusher for AZTEC WELL SERVICING CO., this 13th day of April 1981. To certify which witness my hand and seal of office.

Sally Sandel
Notary Public in and for
San Juan County
State of New Mexico

My commission expires January 3, 1983.



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

DEPCO, Inc.

3. ADDRESS OF OPERATOR

1000 Petroleum Building - Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1120' FNL, 790' FEL (NE/4 NE/4)

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Subsequent Report of Operations ☐

SUBSEQUENT REPORT OF:

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 5 PM 4-8-81. Drilled 12 1/4" hole to 152' KB. Ran 3 jts - 136.24' - 8-5/8" 24# - K55 - R3 - ST&C casing landed @ 148' KB. Cemented w/100 sx Class "B" regular containing 3% CaCl2 & one sack Flocele. Cement circulated to surface. PD 8:30 PM 4-8-81. WOC 12 hrs.

Drilled 7-7/8" hole to 1925' TD. Ran DIL & CNL/FDC w/GR & Caliper logs. Ran 47 jts - 1915.01' - 4 1/2" - 10.5# - J55 - R3 - ST&C casing landed @ 1927' KB. Cmt'd w/265 sx 65/35 Pozmix, 12% gel, 12 1/2# gilsonite/sx followed by 100 sx Class "B" regular. Cement circ'd to surface. PD 8:30 PM. Rig released 9:30 PM 4-10-81. WOC.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. P. Schwenm TITLE Prod. Supt. - So. DATE 4/14/81

Rockies

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

APR 21 1981

NMOCC

*See Instructions on Reverse Side

FARMINGTON DISTRICT

BY _____