TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

.

DEPARTMENT OF THE UNTERIOR OF	5. LEASE NM 01051		
GEOLOGICAL SURVEY SO SO	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or allow back to a different	7. UNIT AGREEMENT NAME Huerfano Unit		
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Huerfano Unit		
1. Oil gas well other 2. NAME OF OPERATOR	9. WELL NO. 144E		
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Basin Dakota		
P.O. Box 289, Farmington, NM 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31, T-27-N, R-9-W NMPM''		
AT SURFACE: 870'N, 840'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO. 15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6428' GL		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Ran 4 1/2" RTTS packer set at 2604' on 2 3/8" tubing. Held 2000#, on backside Cemented w/ 118 cf. cement.

2-9-81: Set RTTS packer @ 2398'. Pressure tested backside to 2000# could not get circ. Cemented w/ 118 cf. cement. Pressured up to 1800#, held ok. Final squeeze. Pressure 1800#, WOC 18 hours.

2-11-81: PBTD 6887'. Pressure tested casing to 4000#, Held Ok. Perfed Dakota: 6615,6621,6627,6652,6710,6715,6722,6739,6776,6813,6839' W/1 SPZ. Fraced w/ 63,000# 20/40 sand, 36,000# 10/20 sand, 43,000 gal. wtr. Flushed w/ 2940 gal. wtr.

Subsurface Safety Valve: Manu. and Type			Set @	
18. I hereby certify that the foregoing is SIGNED Succes	true and correct			
SIGNED N. Pauses	τιτιε <u>Drilling Clerk</u>	DATE	December 17, 1981	
	(This space for Federal or State office	use)		
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE	ARGESTER FOR E	

1.5 1981

TO THE BOOK AND A SERVICE

*See Instructions on Reverse Side