

5 BLM 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

DUGAN PRODUCTION CORP.

ADDRESS OF OPERATOR

P O Box 208, Farmington, NM 87499

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1850' FSL - 1850' FWL

DEC 06 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 37913

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

La Lee Ann

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Gallegos Gallup Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 28, T27N, R13W, NMPM

12. COUNTY OR PARISH 13. STATE

San Juan

NM

PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6090' GL; 6102' RKB

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

RELL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. Four Corners Drilling Company rig #3. Spudded a 12 1/4" hole @ 3:00 PM on 12-3-85. Drilled to 224'. Ran 7 jts. 8-5/8" OD, 24#, J-55, 8 Rd, ST&C casing (T.E. 205.76') set at 218' RKB. Cemented with 200 sx class "B" plus 2% CaCl₂ (total cement slurry 236 cf). P.O.B. @ 8:00 PM 12-3-85. Circulated approximately 2 bbls cement to surface.

Tested surface casing & BOP 600 psi 30 minutes before drilling out - held OK.

RECEIVED
DEC 09 1985

OIL COM
DEC 11 1985

I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE 12-5-85

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

DATE

DEC 6 1985

*See Instructions on Reverse Side

NM0001

FARMINGTON RESOURCE AREA
BY 663