

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTFORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or recomplete a well in a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well  
Oil ☐ Gas ☒ Well ☐ Other ☐

2. Name of Operator

Merrion Oil &amp; Gas Corporation

3. Address and Telephone No.

610 Reilly Avenue, Farmington, NM 87401-2634

(505) 327-9801

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1110' fml &amp; 1580' fel (nwne)

Section 35, T27N, R13W

5. Lease Designation and Serial No.

NM-033047

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

HI ROLL No. 3R (007804)

9. API Well No.

30-045-29977

10. Field and Pool, or Exploratory Area

WAW Fruitland Sand P. C.

11. County or Parish, State

San Juan County, New Mexico

12. CHECK APPROPRIATE BOX (s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

## TYPE OF ACTION

☐ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☒ Other Spud, Csg & TD Reports☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Completion or Recompletion Report and Log form.)

13. Describe Proposed or completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6/30/01 MIRU L&amp;B Speed Drill. Spudded 8-3/4" surface hole at 1:00 PM 6/30/01. Drilled to 126' (had trouble with lost circulation.) Circulate hole clean and TOH. Ran 3 joints (120.30') of 7", 23#, J-55 casing landed at 125' KB. Precede cement with 5 bbls of water. Mix and pump 70 sxs (83 cu.ft.) of Class 'B' with 2% CaCl2 and 1/4#/sx celloflake. Displaced cement with 4 bbls of water. Circulated out 4 bbls of cement to surface.

7/5/01 TD hole at 1415' at 2:30 PM 7/5/01. Circulate hole clean and TOH. Ran 32 joints (1408.68') of 4-1/2", 10.5#, K-55, ST&amp;C casing landed at 1414' KB. Insert float collar at 1368' KB, wash casing to bottom. Circulate bottoms up. Precede cement with 10 bbls of water. Mix and pump 120 sxs (247 cu.ft.) of Class 'B' with 2% SMS and 1/4#/sx celloflake. Tail in with 50 sxs (59 cu.ft.) Class 'B' with 1/4#/sx celloflake. Dropped plug and displaced cement with 22 bbls of water. Plug down at 5:45 PM 7/5/01. Circulate out 15 bbls of cement to surface. (Bumped plug to 1500# float held OK). ND BOP and set slips. Cut off casing. RDMOL. WOCT.

14. I hereby certify that the foregoing is true and correct

Signed

Steven S. Dunn

Title Drlg &amp; Prod Manager

Date 7/9/01

(This space for Federal or State office use)

Approved By

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NACON

JUL 16 2001

K