

DISTRICT I

1625 N. French Dr., Hobbs, NM 87240

DISTRICT II

811 South Frist, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

DISTRICT IV

2040 South Pacheco, Santa Fe NM 87505

**OIL CONSERVATION DIVISION**2040 S. Pacheco  
Santa Fe, NM 87505

WELL API NO.	30-045-30196-00
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil / Gas Lease No.	
7. Lease Name or Unit Agreement Name	BLANCO COM
8. Well No.	5-A
9. Pool Name or Wildcat	BLANCO MESA VERDE

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.	
1. Type of Well:	OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator	FOUR STAR OIL AND GAS COMPANY
3. Address of Operator	3300 N. Butler Ave. Ste 100 Farmington NM 87401
4. Well Location	Unit Letter <u>E</u> : <u>1425'</u> Feet From The <u>NORTH</u> Line and <u>745'</u> Feet From The <u>WEST</u> Line Section <u>2</u> Township <u>27N</u> Range <u>R9W</u> NMPM <u>SAN JUAN</u> COUNTY
10. Elevation (Show whether DF, RKB, RT, GR, etc.)	6189'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐  
 OTHER: spud notice ☒

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPERATION ☐ PLUG AND ABANDONMENT ☐  
 CASING TEST AND CEMENT JOB ☐  
 OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.


Four Star oil and Gas Co. has completed the following in the subject well.

6/01/2000 Spud well at 6:00 pm, drill to 363'

6/02/2000 Run 8 joints of 8.625, J-55, LT&amp;C, #32 to 363'. Pump 520 sacks class B cement at 75psi. Circulated 60 bbls to surface.

Test casing and cement to 1191 psi.

6/13/2000 Run 110 joints of 15.5#, 5.5", K-55 LT&amp;C casing to 4863'. Pump 722 sacks of LITECRETE and circulate 73 bbls to surface.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Arthur D. Archibeque TITLE Eng. AssistantDATE 06/27/2000TYPE OR PRINT NAME Arthur D. ArchibequeTelephone No. 325-4397

(This space for ORIGINAL SIGNED BY CHARLIE T. PEPIN)

APPROVED

BY \_\_\_\_\_ TITLE \_\_\_\_\_

DEPUTY OIL & GAS INSPECTOR, DIST. 4DATE JUN 28 2000

CONDITIONS OF APPROVAL, IF ANY:

✓