

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Angel Peak Extension Formation Sabota County San Juan  
 Initial XX Annual \_\_\_\_\_ Special \_\_\_\_\_ Date of Test 8/19/60  
 Company Astec Oil and Gas Company Lease McClellan Well No. 17-D  
 Unit A Sec. 24 Twp. 20N Rge. 10W Purchaser Southern Union Gas Co.  
 Casing 1 1/2" Wt. 9.5 I.D. 1.000 Set at 6325 Perf. 6376 To 6550  
 Tubing 2 Wt. 4.7 I.D. 1.000 Set at 6361 Perf. Pin Collar To \_\_\_\_\_  
 Gas Pay: From 6376 To 6550 L 6361 xG 0.65 -GL 4135 Bar.Press. 12.00  
 Producing Thru: Casing \_\_\_\_\_ Tubing 2 Type Well Single  
 Single-Bradenhead-G. G. or G.O. Dual  
 Date of Completion: 8/12/60 Packer \_\_\_\_\_ Reservoir Temp. 130

OBSERVED DATA

Tested Through (Pressure) (Choke) (Pressure) Type Taps \_\_\_\_\_

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h <sub>w</sub>	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI						<u>2004</u>		<u>1000</u>		<u>7 days</u>
1.		<u>0.750</u>				<u>301</u>	<u>60 In.</u>	<u>300</u>		<u>1 hr.</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F <sub>t</sub>	Gravity Factor F <sub>g</sub>	Compress. Factor F <sub>pv</sub>	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.303</u>		<u>405</u>	<u>1.000</u>	<u>0.960</u>	<u>1.003</u>	<u>300</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio \_\_\_\_\_ cf/bbl.  
 Gravity of Liquid Hydrocarbons \_\_\_\_\_ deg.  
 F<sub>c</sub> \_\_\_\_\_ (1-e<sup>-s</sup>)  
 Specific Gravity Separator Gas \_\_\_\_\_  
 Specific Gravity Flowing Fluid \_\_\_\_\_  
 P<sub>c</sub> 2012 P<sub>c</sub> 40400

No.	P <sub>w</sub> P <sub>t</sub> (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(F <sub>c</sub> Q) <sup>2</sup>	(F <sub>c</sub> Q) <sup>2</sup> (1-e <sup>-s</sup> )	P <sub>w</sub> <sup>2</sup>	P <sub>c</sub> <sup>2</sup> -P <sub>w</sub> <sup>2</sup>	Cal. P <sub>w</sub>	P <sub>w</sub> /P <sub>c</sub>
1.	<u>301</u>					<u>90601</u>	<u>107900</u>		
2.									
3.									
4.									
5.									

Absolute Potential: 300 MCFPD; n 0.75

COMPANY Astec Oil and Gas Company  
 ADDRESS Box 370, Farmington, New Mexico  
 AGENT and TITLE ORIGINAL SIGNED BY L. M. STEVENS L. M. Stevens, Engineer  
 WITNESSED \_\_\_\_\_  
 COMPANY \_\_\_\_\_

REMARKS



## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- $Q$  = Actual rate of flow at end of flow period at W. H. working pressure ( $P_w$ ).  
MCF/da. @ 15.025 psia and 60° F.
- $P_c$  = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.  
psia
- $P_w$  = Static wellhead working pressure as determined at the end of flow period.  
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  = Flowing wellhead pressure (tubing if flowing through tubing, casing if  
flowing through casing.) psia
- $P_f$  = Meter pressure, psia.
- $h_w$  = Differential meter pressure, inches water.
- $F_g$  = Gravity correction factor.
- $F_t$  = Flowing temperature correction factor.
- $F_{pv}$  = Supercompressibility factor.
- $n$  = Slope of back pressure curve.

Note: If  $P_w$  cannot be taken because of manner of completion or condition of well, then  $P_w$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_t$ .