

R-5676 A
NSL R-5676

F. Loc. 1077/S; 2436/E Elev. 5688 GL Spd. 9/23/30 Comp. 11/25/30 TD 1880 PB

Casing S. 10 @ 20 W Sx. Int. @ W Sx. Pr. 6-5/8 @ 1788 W Sx. T. 1" @ 1760
Csg. Perf. CH 1788-1880 Prod. Stim.

I.P. 4050 MCF/D After 3 Hrs. SICP 555 PSI After Days GOR Grav. 1st Del. 5

TOPS		NITD	Well Log	TEST		DATA					Ref. No.
Kirtland		C-102	Plot X	Schd.	PC	Q	PW	PD	D		
Fruitland		C-103	Electric Log	5/18/67	220	74	121	178	56		
Pictured Cliffs		C-104 X	C-110 X	5/18/67	160	74	119	128	62		
Cliff House			C-122	3/17/68	236	99	185	189	93		
Menefee		Ditr	Dfa	6/17/69	222	74	174	178	69		
Point Lookout		Datr	Dac	4/17/70	226	100	169	181	84		
Mancos			Remarks Nit at and PC	6/17/71	184	67	163	147	104		
Gallup			4 g. per 2 ft	6/17/72	206	70	168	165	74		
Sanostee			Chalco 364	7/17/73	187	70	137	150	56		
Greenhorn			NW 1/4 - R-5676	8/1/75	146	29	126	117	39		
Dakota			R-5676 A	7/2/77	125	4	130	100	14		
Morrison			SE/SW 1/4 Sec 11.	Dine 6-24-81							
Entrada			1/4 Sec 11								
			1/4 F. Garland #4								
			Angel Peak Oil Co.								
			NW 1/4 - 57								
			120 160								

P
o
i Full Kutz PC Co. SJ s 11 T 28N R 11WUC or Southland Royalt Co Lse. Browning Stewart No. 4